



GWAVA

# General Administration Guide

GWAVA 6.5

## Table of Contents

Major New Changes .....	5
How GWAVA works.....	7
How the different Interfaces work .....	7
SMTP Interface.....	7
Web Interface .....	7
GWIA Interface.....	8
MTA Interface .....	8
POA Interface .....	8
Vibe Interface.....	9
WASP Interface .....	9
Choosing an interface for your system .....	9
Creating an Interface .....	10
SMTP Interface.....	11
Web Interface .....	17
GWIA Interface.....	20
MTA Interface .....	23
POA Interface .....	26
Vibe Interface Install .....	32
WASP Local Interface .....	35
WASP Remote Interface.....	37
General Administration.....	40
GWAVA Management Console .....	40
Dashboards .....	40
Dashboard Control Panel .....	41
Configuring and customizing Dashboards .....	42
Quarantine manager .....	43
Bookmarks .....	44
Documentation .....	44
System Management .....	44
System Management .....	45
Licensing.....	45

Admin accounts.....	45
System Information.....	45
System Alerts .....	45
Reports.....	46
Message tracking .....	48
Default settings .....	49
Online updates.....	49
Package manager .....	49
Advanced .....	50
System Tools .....	50
Server/Interface Management .....	53
Server management.....	53
Advanced Statistics settings.....	55
Advanced SMTP Relay Configuration.....	56
Proxy Configuration .....	56
IP Configuration .....	56
SSL .....	57
Advanced.....	57
Configure Domains.....	58
Server control.....	58
Antivirus agent setup .....	58
IP Reputation Setup .....	59
Logs .....	59
Wizards .....	60
Manage interfaces .....	60
Interface settings .....	60
Scanner / Policy Management .....	61
Policy Manager .....	61
Unlocking the Policy Manager .....	64
How Mail flows through a policy tree; Qualification .....	66
Multi-Tenancy and Policy Trees .....	66
Specific Policy Settings.....	68

Scanner Management.....	71
General Settings.....	71
Notification .....	73
Scanning configuration .....	73
Antivirus .....	73
Antispam .....	74
Spam Detection.....	74
SURBL .....	74
RBL .....	75
IP Reputation .....	75
SPF.....	76
Denial of Service.....	76
Conversation Tracking.....	77
Spam Reporting.....	78
Text filtering .....	79
Subject + Body.....	79
Subject or Body .....	79
URL Filtering .....	80
Authentication Filtering .....	80
Body Filter .....	80
MIME filtering .....	81
Raw.....	81
Message Header .....	81
Oversize.....	82
Undersize .....	82
Fingerprinting.....	83
Image Analyzer.....	84
Attachment types.....	85
Source address filter (from:) .....	86
Destination address filter (to:) .....	86
IP Address Filter .....	87
Message services .....	87

Exceptions .....	90
Source address (From:) .....	90
Destination address (to:) .....	91
Message subject.....	91
Message text.....	91
Message header .....	91
Message source .....	92
IP Address.....	92
Authenticated User .....	92
GWAVA Quarantine system .....	93
User interface.....	93
Administrator interface.....	94
Appendix .....	109
Padlock State Checkboxes .....	109
Policy Inheritance.....	109
Scanner Configuration: Hierarchy and Inheritance .....	110
GWIA and SMTP interfaces on the same box .....	113
SMTP interface ports .....	113
GroupWise paths .....	114
Linux.....	114
Squid configuration file changes.....	114

**Copyright Notices** The content of this manual is for informational use only and may change without notice. GWAVA Inc. assumes no responsibility or liability for any errors or inaccuracies that may appear in this documentation. Windows® is a registered trademark of Microsoft, and copyrighted by Microsoft. GroupWise® and SUSE® are registered trademarks of Novell, and copyrighted by Novell, inc. All rights reserved. GWAVA is a registered trademark.

### **Major New Changes**

GWAVA has changed a few core ways that scanners are implemented in the system. This was completed to facilitate multi-tenant systems, or systems containing more than one active domain, which require different settings.

To enact this new ability, several changes were necessary. The scanner is no longer associated with any interface, domain, or server. GWAVA uses 'policies' to manage to manage different scanning configurations. Policies enable more comprehensive control over scanning from a broad scope down to a granular, user by user, level. See the [Policy Manager](#) section for details.

GWAVA also includes a new image analyzer which can scan and flag offending images. As with other configurations, the image analyzer offers the same actions for mail in the GWAVA system: block, quarantine, notify, and flag. The image analyzer is an additional service to the GWAVA scanning system and requires an additional license. See a GWAVA sales representative for details.

GWAVA has changed the way it installs. GWAVA has a native installer supporting both 32 bit and 64 bit installations for windows. For Linux, GWAVA is provided in an RPM which installs the system automatically with the appropriate version.

GWAVA's New Web interface.

GWAVA has included a new Web Interface which allows the GWAVA system to connect to an ICAP enabled proxy to filter web traffic. The Web Interface can filter or block based on URL as well as specified keywords found on web pages. User access may also be restricted through user authentication.

## **How GWAVA works**

GWAVA is an anti-malware and content management solution which provides complete protection for your mail system through a real time interface. The Signature scanning engine in GWAVA allows for instant protection and regular spam definition updates with virtually no false-positives. The Signature scanner recognizes spam due to a managed definition base which can also recognize most viruses before the mail reaches the virus scanner, adding an extra layer of protection.

GWAVA can fit its scanner to any mail system through a SMTP interface to protect the mail system from attack and wasted bandwidth. In addition, GWAVA is able to implement its scanner in the following GroupWise agent interfaces:

- GWIA interface
- MTA interface
- POA interface
- WASP (WebAccess) interface
- Vibe interface

## **How the different Interfaces work**

The different scanning interfaces offered by GWAVA all utilize the same scanning engine in the base of the GWAVA system, but each interface is configured separately to integrate to the different components they are named for. These different scanning interfaces are briefly explained below.

### **SMTP Interface**

The SMTP interface allows incoming and, or, outgoing mail to be intercepted, scanned, and filtered completely independent of the mail system. This setup has the distinct advantage of relieving the mail system of unnecessary and unwanted traffic, leaving the mail system resources open to function with greater performance and security.

The SMTP interface adds a scanning layer between any mail system's SMTP agent and the internet. Outbound mail is forwarded through the GWAVA SMTP, (like a proxy), which can scan the mail and then send messages to the internet. Incoming mail is first received by the SMTP interface which then sends the filtered mail to the SMTP agent. This interface allows GWAVA to act independently of your mail system. If used behind a firewall, see the [appendix](#) on suggested open ports.

### **Web Interface**

The Web interface is a scanner applied to the web traffic passing through an ICAP enabled proxy. When enabled and connected to an active ICAP proxy, the Web Interface can filter web traffic, scan pages for keywords and block offending pages, require user authentication and deny access to specified users, and block specific URLs. This interface adds a layer of control and limits or defines access to the internet through the network. Because this interface scans web pages instead of messages, many settings do not apply to this scanner, and configuring mail filters for this interface is not recommended. For instance, utilizing anti-spam scanning on the web interface will slow down the system and effectively block everything. See the applicable sections for configuration settings.

## **GWIA Interface**

The GroupWise Internet Agent interface, or GWIA interface, intercepts the mail flowing through the GWIA folder structure, scans the mail, then passes clean mail back to the GWIA for normal mail processes. The point of interception comes directly after the GWIA receives the mail from the internet source, or right before the connected GWIA sends the mail across the internet. The GWIA interface does not directly receive mail or send mail, and has no connection to the internet whatsoever. GWAVA's GWIA interface instructs the GWIA to place mail it has received into a holding folder structure, called the 3<sup>rd</sup> folder, where the mail waits to be scanned by GWAVA. Once the mail has been scanned and sorted, GWAVA places the clean message files into the proper folder, where the GWIA then moves the incoming mail to the MTA and the outgoing mail to the internet destination, as part of its normal process. Clean messages are passed through the system as normal, with no alterations to the file.

Because the GWIA interface is integrated in the base folder structure, and not in the actual processes of the GWIA agent itself, there is no start or stop order for GWAVA or the GWIA. If a GWIA interface has been created and installed correctly, then if GWAVA is not running while the GWIA is attempting normal operation, then mail received from the internet, and mail waiting to be sent to the internet, will queue up in the holding folders created for the interface. Once GWAVA is started, the queued mail will be processed and sent to the internet or the MTA as normal.

## **MTA Interface**

The Message Transfer Agent interface integrates into the process of the actual GroupWise agent, adding the anti-malware scanner into the normal processes of the MTA. GWAVA utilizes the GWMTAVS virus scanning API provided by Novell. To utilize this API, GWAVA invokes the virus scanning switches in the MTA startup file, calling first GWMTAVS, which then loads the GWAVA MTA interface. Each file passing through the MTA is handed to the GWMTAVS and then the GWAVA MTA interface, which scans the message, reporting to the GroupWise MTA if the message should be blocked or is clean, and can be passed through to the rest of the system. Clean messages are passed through the system as normal, with no alterations to the file.

Because of the nature of the API and the loading process, there is an order to starting and stopping the GroupWise MTA and GWAVA with a MTA interface. Because it is called during start and not controlled by the MTA on shutdown, the GWAVA interface is the first started, and the last stopped in order to prevent the GroupWise MTA from failing to start or stop. The order to start a GroupWise MTA with an attached GWAVA MTA interface is, first to start GWAVA, and then start the MTA. To shutdown the MTA and GWAVA, first stop the MTA, then shutdown GWAVA.

**Due to environmental variables, the MTA interface will not function on Windows GroupWise systems.**

## **POA Interface**

The Post Office Agent interface is the only interface in the GWAVA suite which does not implement a real time scanner. Because there is no API or process that allows the Post Office to be scanned in real time, GWAVA has created a scheduled interface which can periodically sweep the Post Office for malware and unwanted or unapproved messages and files.



Utilizing a trusted application key generated by the system administrator, the POA interface enters and scans each user's post office and messages individually. The POA interface can be set on a reoccurring schedule or set to run as a single use job, and has the ability to exclusively target or exclude specific user mailboxes as desired for security or policy. Clean messages and files are left completely unaltered. The POA interface requires the POA to be running in order to operate, but has no start or stop order associated with the operation.

### **Vibe Interface**

GWAVA can implement a scanning interface into the Novel Vibe system to scan correspondence and work flow. All input text and transferred files can be scanned through the Tomcat servlet. Essentially, all text messaging, emails, threaded conversation, sent files, and attachments can be scanned by GWAVA.

Files and messages which are caught by the interface will be blocked, deleted, or quarantined according to the settings and configuration of the interface. Notification and released messages and mail will be sent through the email system, allowing the Vibe interface to be effortlessly moderated, protected, and controlled according to company policy.

### **WASP Interface**

The GroupWise WebAccess interface integrates into the WebAccess system by hooking into the WebAccess servlet, working between the message composition interface of WebAccess and the WebAccess agent. This allows WASP2 to scan all messages for viruses and any defined content before they are sent to the GroupWise server. If a problem is found, the message will not be sent and the user is notified of the problem.

The WASP interface scans the message as soon as the user clicks 'send' in the WebAccess interface. In case of a problem, the notification that WASP sends to the user will inform them which part has the targeted problem, so they may correct the blocked item and send their message.

WASP scanning interfaces can be operated remotely to the Web Access server if desired, though there must be a quick and reliable network connection between the WebAccess machine and the machine running GWAVA.

### **Choosing an interface for your system**

The most recommended scanning interface for any mail system is the SMTP interface, which has the highest performance and least intrusion while providing several services that are not available to the GWIA, MTA, and POA interfaces. However, the SMTP interface may not be the best fit for your system.

Determine what protection and service needs you have for your GroupWise system in order to determine which interface would fit best. The POA interface will only protect the Post Offices on a scheduled basis, and should never be relied on for full protection of your system. The MTA interface will provide protection between domains and different post offices as well as external mail, but the MTA interface also has a specific start and stop process, connects directly into the GroupWise Agent structure, and cannot provide the service which appends a specific signature to the end of each message sent.

The GWIA interface sorts all mail passing through the GWIA, which protects the GroupWise system from all external mail threats. The GWIA interface provides almost all options available, (except connection dropping), including the signature service, and does so without connecting directly into the GroupWise agent structure or requiring a start and stop procedure. If the client computers connected to the GroupWise system are equipped with virus protection software of their own, there is little advantage to choosing an agent interface other than the GWIA or SMTP interface.

The SMTP interface is designed to provide protection for any email system in the market. The simplest way to implement the SMTP interface is to use it in conjunction with the GWAVA Appliance, which completely separates the GWAVA system from any mail structure.


The SMTP interface acts as a proxy for the SMTP Gateway of your mail system.

The SMTP interface and GWAVA appliance are meant to be placed in front of the current GWIA or SMTP Gateways for the mail system. Incoming email sent to your domain will first go to the GWAVA appliance, which scans the messages and then sends clean email to the GWIA or SMTP Gateway. Mail sent from your domain can also pass through the SMTP interface and the GWAVA appliance, which sends the email to the internet.

Contact the sales representative for your area if you wish to implement the GWAVA Appliance and SMTP interface.

## Creating an Interface

Installing an interface is the next step in creating a functioning GWAVA system, followed by domain configuration, (covered in the SMTP Interface wizard section), and licensing. If the GWAVA server is to be used in a trial period, the interface will be automatically placed into bypass mode as soon as the trial period is over unless a license has been applied.



The Interface creation wizards, (found under Server/Interface Management | Wizards | Install/create new interface), walk through the steps and information required to install the different interfaces for your system. Select the desired interface and follow the instructions to install.


## SMTP Interface

The SMTP interface is the most recent option to the GWAVA system, and allows the incoming and, or, outgoing mail to be intercepted, scanned, and filtered independent of the mail system. This setup has the distinct advantage of relieving the mail system of unnecessary and unwanted traffic, leaving mail system resources open to function with greater performance and security.

The SMTP interfaces adds a layer between the GWIA, or any other mail system's SMTP sending agent, and the internet. Sending mail is forwarded through an SMTP proxy, which then sends the filtered, clean mail to the original recipient. Incoming mail is scanned via the SMTP interface, which then sends the filtered and clean mail to your mail system, unaltered. These interfaces allow GWAVA to act independently of your mail system.

The SMTP interface will only work if your MX record points to the GWAVA SMTP interface for mail delivery, and if your domain and mail system SMTP are listed correctly in your GWAVA system.

GWAVA SMTP will then forward the clean mail to the SMTP Gateway specified during server activation. To view or change the domain and SMTP for your Mail system, go to [Server/Interface Management](#) | [<Server Name>](#) | [Server Management](#) | [Configure domains](#).



The default domain specified during Server Activation will be specified. Additional domains may be added through the new domain addition field along the top of the screen. As always, make sure you save all desired changes made to the page before browsing to a different section of the management console.

The Mail relay agent SMTP Server and Default domain **MUST** be correct for your system. If you have multiple domains, you must list the additional domains. GWAVA will only accept mail for the listed domain(s). Domains can be deleted or removed from the system by selecting the domain, then the red 'X' next to the selected domain name.

Select the desired domain to expand and modify the settings for the desired domain. The default domain settings are shown below.

When a domain is selected, it is expanded and allows for multiple settings for user mail validation.

gwava.com ✖

Default domain for this server

Host names for this domain

Server scope

Recipient validation method

Recipient authentication method

SMTP server list

smtp server	auth username	auth password	no encryption	encryption	Receive mail/authenticate	server role	order
192.168.1.101	Chris	••••	no encryption	no encryption	Receive mail/authenticate	0	0

LDAP lookup list

Search all LDAP servers with the same order value

ldap server	username	password	no encryption	encryption	scope	DN search base	search fields (optional)	order
			no encryption	no encryption	sub tree			0

GWAVA checks for valid users for each message received, blocking those which are undeliverable due to an incorrect domain or nonexistent user for each domain. GWAVA must have a connection to an active SMTP server for each domain to verify the users. LDAP lookup is also supported. If users or messages are received which do not contain domain information, GWAVA checks these users against the default domain. Be sure to set the default domain for your system.

Multiple SMTP or LDAP servers are supported for failover purposes. If a SMTP server is unavailable GWAVA will send messages to the next available SMTP server listed according to the 'order' value. The 'order' values lowest numbers first, usually with the default SMTP listed as '0', second as '1', and so on.

If the SMTP server requires authorization then the user name and password must be provided for each SMTP server listed. Generally, the authorization username and password will not be needed unless the SMTP server has been specifically configured to only accept authorized connections.

GWAVA shares the user list for each domain between the GWAVA modules, and specific SMTP servers can be selected to serve in different roles for each system, such as using one to receive mail, digests, and notifications, while another is used by QMS to authenticate users. Default settings allows SMTP servers to serve in all roles.

If the SMTP server requires encryption such as TLS or SSL, the setting must be correct.

If the GWAVA server is part of a GWAVA system network with multiple GWAVA servers, then the information from the domains can either be shared across the GWAVA network, or it can be made specific to this one server. For most all systems the option of 'Global' will work sufficiently.

## LDAP (optional)

GWAVA supports the option to use LDAP user authentication instead of SMTP authorization for QMS authorization and recipient verification. In general, this will not be required for most systems; LDAP information is only required if you wish to use LDAP for lookup or authentication.

In order to use LDAP for user lists and authorization, the LDAP lookup information must be filled in.

ldap server	username	password	encryption	DN search base	search fields (optional)	order
ldap1.gwava.com	cn=admin,o=gwava	•••••	no encryption ▼	ou=users,o=gwava		0 ✖

For the LDAP server connection address, place DNS name or IP address of the server

The username and password needs to be a full LDAP username including context. The user should have administrator rights.

The DN search base can be set to specify the LDAP tree where GWAVA will begin to search for objects. For eDirectory this field can be left blank, though if set, it specifies a starting point for the search in the LDAP tree. (For instance: ou=users,o=gwava) If using Active Directory the DN **must be set** for the user list to work. (ie. Cn=users,dc=exg,dc=gwava,dc=com)


Search fields are usually not necessary for any system to setup, but can be useful if desired. By default most LDAP servers (including eDirectory and Active Directory) have an attribute applied to an object of the type "mail" which contains the object's or user's email address. If you have email addresses for users stored under an attribute other than mail you can specify the possible attributes by separating them with commas.

In the example below the LDAP server is set to search for the attributes 'mail' and 'secondarymail'.


ldap server	username	password	encryption	DN search base	search fields (optional)	order
10.1.5.12	cn=admin,o=robtain	•••••	no encryption ▼	ou=users,o=robtain	mail,secondarymail	0 ✖

Once the Domains have been properly configured for the system the SMTP interface, and any other interfaces, may be properly created.

Open the Interface creation wizard, (found under Server/Interface Management | <Server name> | Wizards | Install/create new interface), and select the SMTP Interface and follow the instructions to install.



The SMTP interface creation wizard informs you of the information you must know to successfully create the interface.



The **Interface Name** is whatever you wish the interface to be named in the GWAVA server.

The **IP listen address** is the address that the SMTP interface will bind to and listen on. It

should be the address of the GWAVA server. This should also be listed on the MX record for your



domain. (If the SMTP interface resides on the same machine as the GWIA, then the GWIA must be changed to listen on a port other than 25, as the SMTP interface uses that port. Then inform GWAVA that the 'Mail relay agent SMTP server' – or GWIA – listens on a port other than default. This setting is found on the Server Configuration page. Append the port at the end of the address with a colon. (10.1.1.10:26) See <http://support2.gwava.com/kb/?View=entry&EntryID=1215> for more details.

**Allowed relay addresses** are the source addresses which are allowed to send mail through the GWAVA SMTP interface. Your mail system SMTP address should be listed here, as well as any other mail sending source for your domain. Mail coming from these addresses will be treated as outbound mail. No source but these listed addresses will be allowed to send mail through the SMTP interface.


The red 'X' removes listed address ranges and the blue 'add...' link provides an extra address/ range box.

**IP Reputation, RBL, and SPF** drop at connection settings are recommended as default. This dumps any incoming message that fails these initial incoming tests, saving bandwidth and performance.

Select your default preferences, and click 'Next'.

Set the default actions for viruses and spam. These settings can be changed after interface creation.

Click 'Next'.



Review and confirm your settings. If you wish to make changes, use the ‘**back**’ button on your browser, correct the information, and Next.

The screenshot shows a web-based configuration window titled "Create new SMTP interface". At the top, a progress bar indicates the current step is "Confirm selections", with previous steps "Welcome", "Interface settings", and "Scanner defaults" completed, and "Install" and "Finished" yet to come. The main content area contains a summary of the configuration: "The requisite information has been collected and is ready to be deployed. If you are satisfied that the installation information is correct, press the install button to commit the installation procedure to the GWAVA network." Below this, the following settings are listed: Scanner name: SMTP; Install to server: TEST7 (Windows); IP listen address: 0.0.0.0; Allowed relay addresses: 127.0.0.1, 192.168.\*.\*, 172.16.\*.\*, 10.\*.\*.\*; IP Reputation: Yes; RBL connection drop: Yes; SPF connection drop: Yes; Setup virus scan defaults: Yes; Setup antispam defaults: Yes. At the bottom, there are two buttons: "<< Previous" and "Install >>".

Click ‘**Install**’ to continue.


The screenshot shows the same "Create new SMTP interface" window, but now the "Install" step is active in the progress bar. The main content area displays a message with a loading icon: "Installing interface, please wait...". Below this, a note states: "This process may take a few minutes. Please be patient and do not change your browser page during this step."

Wait while the installation completes.

The screenshot shows a new window titled "SMTP interface installation finished". The progress bar at the top now shows "Finished" as the final step, with "Install" completed. The main content area contains the text: "Interface installation is now complete. You can manage the interface specific properties via the Interface Management menu. The scanning and filtering settings can be located and managed under the Scanner / Policy Management menu."

Once installation is complete, click ‘Home’ at the top left of the page to refresh the system, then navigate to the Server/Interface Management | <Server Name> | Manage interface folder to view your new SMTP interface.






Your SMTP interface is now created and ready, and the policies are automatically managed until changed. For further configuration, see the [‘Policy Manager’](#) section.

As soon as the MX record pointing to the GWAVA SMTP is active, the SMTP interface will begin filtering mail.

## Web Interface

The Web Interface allows GWAVA to filter web traffic. The Web Interface can search all web traffic to block URLs, key words in web page text with body filtering, or it may be used to limit traffic through web user authentication. The Web interface works in conjunction with an existing ICAP enabled proxy, such as squid.

To install the Web Interface, select the Web Interface from the list and click ‘Continue’.



The Web Interface requires a connection through ICAP to the existing web proxy. If using squid, the configuration file needs to be modified. (See the [squid configuration file addition in the appendix.](#))

After reviewing the necessary changes needed, click ‘Next’ to continue.

**Create new ICAP interface**

Progress: Welcome >>> **Interface settings** >>> Scanner defaults >>> Confirm selections >>> Install >>> Finished

Scanner Name:

Install on this server: WIN-CKMVNM9U5HB (Windows)

IP listen address:

<< Previous    Next >>

Name the interface as desired and will not affect scanning.

The IP listen address is the address that the web interface will bind to and listen on. This should be the address of the machine where GWAVA is housed, or the desired interface on machines connected to multiple networks.

**Create new ICAP interface**

Progress: Welcome >>> Interface settings >>> **Scanner defaults** >>> Confirm selections >>> Install >>> Finished

Your GWAVA system already has policies installed. Please choose whether you would like to share an existing policy configuration, or create a new policy with its own independent configuration for this interface.

☒ Create a new policy for this interface  
☐ Share an existing policy

---

You can quickly setup the scanner with some of the most common default security options

☒ Stop Viruses


Enabling virus scanning includes enabling virus scanner services and detecting file types that frequently include viruses with attachment type scanning (i.e. \*.vbs, \*.pif, \*.exe etc) and fingerprinting of attachments.

[+ advanced settings](#)


<< Previous    Next >>

It is highly recommended to create a new policy for the Web Interface. Due to the architecture and use of the interface, many of the tests and options will not apply and may only serve to slow-down web service. One such option is the spam scanning engine, which, due to keywords on web pages, will end up blocking nearly everything and drastically slow down service. It is NOT recommended to scan for spam on the internet. Setting up an individual setting and then configuring it for the host system is highly recommended.


Though the Web Interface is subject to all the different scans and filters in the GWAVA system



Review the information and click 'Install' to create the interface. Select 'Previous' to correct or change any information.



Wait for the ICAP interface to install.




Once the interface has been installed, its settings can be managed through the **Scanner | Policy Management** menu.

## GWIA Interface

To install a GWIA interface, you must tell the wizard where the active GWIA directory and the GWIA configuration file are located. The GWIA interface puts startup information in the GWIA configuration file and adds the 3<sup>rd</sup> directory to the GWIA directory structure. To make the changes to the GWIA configuration file active, the GWIA must be restarted after the installation is complete.

Name the interface and provide the locations to the directory and file required. Use the example paths as your guide, though they are only examples and will differ from your actual paths. Always double-check your paths to ensure that the interface will install correctly.



The screenshot shows a wizard window titled "Create new GWIA interface". The progress bar at the top indicates the current step is "Interface settings", with previous steps being "Welcome", "Scanner defaults", "Confirm selections", "Install", and "Finished". The main area contains four input fields:

- Scanner Name:** gwia
- Install on this server:** gwava6
- GWIA Startup File:** /opt/novell/groupwise/agents/share/gwia.cfg  
Example: /opt/novell/groupwise/agents/share/gwia.cfg
- GWIA Path:** /mail/dom/wpgate/gwia  
Example: /mygwdomain/wpgate/gwia/

At the bottom, there are two buttons: "<< Previous" and "Next >>".

If the directory path is incorrect, your mail will not flow after the GWIA has been restarted to enact the changes.

Select your basic scanning setup. All the default options are shown below and are fairly self-explanatory. The virus and basic spam scanning options are for setup purposes only. These can all be changed and customized after the interface setup is complete. There are many other options to fine-tune the interface which are only available after the interface has been created. Select the basic setup options you wish to use as default and click Next.

The screenshot shows a wizard window titled "Create new GWIA interface". The progress bar at the top indicates the current step is "Scanner defaults", with previous steps being "Welcome", "Interface settings", and "Confirm selections", and subsequent steps being "Install" and "Finished".

The main content area contains the following text and options:

Your GWAVA system already has policies installed. Please choose whether you would like to share an existing policy configuration, or create a new policy with its own independent configuration for this interface.

- ☒ Create a new policy for this interface
- ☐ Share an existing policy

---

You can quickly setup the scanner with some of the most common default security options

☒ Stop Viruses

Enabling virus scanning includes enabling virus scanner services and detecting file types that frequently include viruses with attachment type scanning (i.e. \*.vbs, \*.pif, \*.exe etc) and fingerprinting of attachments.

[advanced settings](#)

---

- ☐ Quarantine infected messages
- ☒ Block attachments with file names commonly associated with viruses (\*.exe, \*.pif, \*.vbs etc)
  - ☒ Quarantine messages blocked because of attachment names
- ☒ Detect and block attachments commonly associated with viruses (fingerprint exe, pif, com etc)
  - ☒ Store fingerprint blocked messages in the quarantine system

---

☒ Stop Spam

Enabling spam detection includes enabling the heuristic detection system, SURBL, RBL, SPF and IP reputation features in GWAVA.

[advanced settings](#)


---

- ☒ Enable primary automatic spam training services
- ☒ Enable antispam service
  - ☒ Quarantine messages identified as spam
  - ☒ Quarantine messages identified from bulk mail sources
- ☒ Enable RBL service
  - ☐ Quarantine messages detected with RBL
- ☒ Enable SURBL service
  - ☐ Quarantine messages detected with SURBL
- ☒ Enable SPF service
  - ☐ Quarantine messages detected with SPF
- ☒ Enable IP reputation service
  - ☐ Quarantine messages detected with IP reputation

---


At the bottom of the window, there are two buttons: "<< Previous" and "Next >>".

The wizard will ask for confirmation on the information provided. Double check all information and paths to ensure that the interface will function correctly.




Select the install button when you have verified the information.

The wizard will display this page while it is working.




DO NOT browse away from the page until the next page is displayed showing a confirmation that the process is complete and detailing instructions to move forward.



The interface installation is now complete and the interface is now available for fine-tuning and customization.

## MTA Interface

The GWAVA MTA interface can only be installed on a Linux platform. To create an MTA interface, select the MTA interface from the wizard and click next.



The screenshot shows the 'Create new MTA interface' wizard at the 'Welcome' step. The progress bar at the top indicates the following steps: Welcome, Interface settings, Scanner defaults, Confirm selections, Install, and Finished. The main text area contains the following information:

Welcome to the MTA scanner creation wizard.

A GWAVA MTA mail scanner is a program that intercepts mail at a GroupWise MTA and hands the messages on to a GWAVA scanner service for inspection. Once each message has been scanned the MTA mail agent is then responsible for blocking the message or allowing it to pass.

To ensure a smooth installation of this agent, some information about your GroupWise system needs to be supplied. You may also undertake some of these steps manually after the GWAVA network has been configured if you wish to maintain control of the process yourself.

Prerequisites:

- ☐ GWAVA installed on the server that runs the MTA
- ☐ Provide local path on the host server to the MTA startup file\*
- ☐ Provide local path on the host server to the library directory (Linux only)\*
- ☐ Provide local path on the host server to the MTA program files\*


\* These items are required for automatic installation

Post install:

After configuring the GWAVA MTA agent, it is necessary to restart the target MTA, as the GWAVA mail agent is auto-started by the MTA. You will be reminded of this at the end of the setup wizard.

At the bottom, there are two buttons: '<< Previous' and 'Next >>'.

MTA interface creation lists the information that is required. The paths to the MTA startup and program files as well as the path to the library directory must be provided.



The screenshot shows the 'Create new MTA interface' wizard at the 'Interface settings' step. The progress bar at the top indicates the following steps: Welcome, Interface settings, Scanner defaults, Confirm selections, Install, and Finished. The main text area contains the following information:

Scanner Name: MTA

Install on this server: gwava6


MTA Startup File: /opt/novell/groupwise/agents/share/domain.mta  
Example: /opt/novell/groupwise/agents/share/domain.mta

GWMTA Program Location: /opt/novell/groupwise/agents/bin/  
Example: /opt/novell/groupwise/agents/bin/

GroupWise Library Programs Location: /opt/novell/groupwise/agents/lib/  
Example: /opt/novell/groupwise/agents/lib/


At the bottom, there are two buttons: '<< Previous' and 'Next >>'.

Provide an interface name and the paths to the files listed, (default suggestions are shown, but are not always correct for every system). Use the example paths as a guide, but know that the paths will differ from system to system.



Set your desired settings and click 'Next' to progress to the next page.


Due to environmental variables, the MTA interface will not function on Windows GroupWise systems.




Double check and confirm the information provided.



Once the information has been confirmed, select install.




Wait until the following page is displayed. Your interface is installed and ready to use following a restart of the MTA.




## POA Interface

To install a POA scheduled interface, select the POA interface from the wizard menu and click next.




The POA interface connects directly to the POA through the IMAP interface. As such, it requires a trusted application key to be created and IMAP must be enabled and open on the POA. Download and install the TRUSTKEY application and generate the Trusted Application key. To generate a trusted application key, you must run the TRUSTKEY application from a windows workstation that is logged into the GroupWise system with Administrator rights. TRUSTKEY also requires access to the wpdomain.db file. If installing on Linux, this must be accessible through a SAMBA share.

Click on the TRUSTKEY install link, and save then run the trustkey.exe application.




Click 'Next' and read the information provided before continuing.



The Trustkey application will create a trusted application key for GWAVA to access the Post Office with administrator rights. The information dialog also details exactly what is required to create the trusted application key.



Click 'Next' to continue to the application creator window.



Browse to the domain directory containing the active wpdomain.db. This directory must be accessible from the Windows workstation where the TrustKey application is running. The Windows box also must be logged into the GroupWise system via the Novell client, with administrator rights. On Linux, this directory must be accessible through a SAMBA share.


After browsing to and selecting the wpdomain.db file, click 'Create Trusted Key'.

The TrustKey application will create a trusted application key and automatically copy it to the clipboard as well as display it in the 'Generated Key' box.



Paste the copied trusted application key into the POA interface creation wizard and fill out the post office job name as well as the IP address of the Post Office Agent. The IP address must have the IMAP port specified as shown if it is not default. (Default: 143)

The POA Job is not configured after creation. Ensure to continue to the configuration page and complete the required configuration and enable it or the interface will not run.



**IMPORTANT:** On the creation page, ensure that the 'Stop Viruses' box is checked, and then expand the 'advanced settings' link and **uncheck all other boxes**. If the interface is configured to delete email containing attachments, all mail with attachments contained in the fingerprinting and attachments lists will be removed from the post office. Removed mail may be unrecoverable.

The screenshot shows the 'Create new POA interface' window with the 'Scanner defaults' step selected in the progress bar. The window title is 'Create new POA interface'. The progress bar shows: Welcome >>> Interface settings >>> **Scanner defaults** >>> Confirm selections >>> Install >>> Finished. The main content area says: 'You can quickly setup the scanner with some of the most common default security options'. There is a checked checkbox for 'Stop Viruses'. Below it, a text block explains: 'Enabling virus scanning includes enabling virus sanner services and detecting file types that frequently include viruses with attachment type scanning (i.e. \*.vbs, \*.pif, \*.exe etc) and fingerprinting of attachments.' Below this is a link for 'advanced settings'. A red arrow points to a group of settings under 'advanced settings' which are currently unchecked: 'Quarantine infected messages', 'Block attachments with file names commonly associated with viruses (\*.exe, \*.pif, \*.vbs etc)' (which has a sub-checked box for 'Quarantine messages blocked because of attachment names'), 'Detect and block attachments commonly associated with viruses (fingerprint exe, pif, com etc)', and 'Store fingerprint blocked messages in the quarantine system'. At the bottom are '<< Previous' and 'Next >>' buttons.


After verifying that the interface creation page looks identical to the one shown above, click 'Next'.

The screenshot shows the 'Create new POA interface' window with the 'Confirm selections' step selected in the progress bar. The window title is 'Create new POA interface'. The progress bar shows: Welcome >>> Interface settings >>> Scanner defaults >>> **Confirm selections** >>> Install >>> Finished. The main content area says: 'The requisite information has been collected and is ready to be deployed. If you are satisfied that the installation information is correct, press the install button to commit the installation procedure to the GWAVA network.' Below this is a table of installation details:


Install to server	gwava6test (Linux)
Job name	POA scanner
Connection address	192.168.1.101
Trusted Application Key	1302210102DB00008473EF7E12788DE71202210202DB0000A88124D12F58DCE
Setup virus scan defaults	Yes

At the bottom are '<< Previous' and 'Install >>' buttons.

Verify the specified information and select 'Install' if the information is correct. If you need to correct anything, use the 'Previous' button.



Follow the instruction to wait until the success page is displayed.



Once the job has been completed, click on the 'home' link at the top left of the page to refresh and navigate to the 'Scanner / Policy Management' menu and select the new interface and 'Job Config' to complete configuration.

The first task to complete on the configuration page is to enable the job. If the job is not enabled, it will not run.

This page configures the job to include or exclude specific users, folders, and the job start time. Note: the POA job may cause the Post Office response time to lag, causing any connected clients to become sluggish. It is best to schedule the Post Office job to run during off hours, or at times when the Post Office is not under load.

**Job Config**

☐ Enable Job

Job Name: POA scanner

Trusted Application Key: 1302210102DB00008473EF7E12788DE71202210202DB0000AB8124D1:

POA Hostname:Port: 192.168.1.101:142

☒ Scan Users  
☒ Scan Resources  
☒ Scan Trash  
☒ Expunge purged items

Job Frequency: Run Once

Job Date: 14 Jan 2012

Time to run job: 00 : 00

Run job immediately: ☐

Scan messages in date range: All days

Scan these users: All Users

Remove Selected User

User:  Add

Scan these folders: All Folders

Remove Selected Folder


Folder:  Add

To add specific users to be included, or to exclude specific user mailboxes, you must provide the mailbox name.

The same applies for Folders. If you wish to include or exclude specific folders, you must supply the folder name.

To specify whether the job will apply to all users or folders, only specified users or folders, or all but the specified users or folders, or to set a date range to scan through, use the drop-down menu for each section.

Once you have enabled and configured the job, make sure to select the 'save changes' button at the top of the window before browsing away from the page. Once the changes have been saved, the changes will be sent to the GWAVA system and will become active within a couple of minutes.



To access the POA Job settings page just described, browse to Server / Interface Management | <server name> | Manage Interfaces and expand the POA interface and select the 'Interface settings' object under the 'Configure POA job settings' folder, as shown.

The screenshot shows the 'Job Config' page for the 'POA scanner' interface. The left sidebar contains a navigation tree with the following structure:

- Home Pages
  - Home dashboard
  - Dashboards
  - Quarantine manager
- Bookmarks
- Documentation
- System Management
- Server / Interface Management
  - SLES11-32 (Linux)
    - Server management
    - Wizards
    - Manage interfaces
      - GWIA
      - MTA scanner
      - POA scanner
        - Interface settings**
        - Interface uninstall

- Scanner / Policy Management
- Policy manager
- GWIA
  - General settings
  - Scanning configuration
  - Message services
  - Exceptions
- MTA scanner
  - General settings
  - Scanning configuration
  - Message services
  - Exceptions

The main content area is titled 'Job Config' and contains the following settings:


- ☐ Enable Job
- Job Name: POA scanner
- Trusted Application Key: 1302210102DB00008473EF7E12788DE71202210202DB0000AB8124D1
- POA Hostname:Port: 192.168.1.101
- ☒ Scan Users
- ☒ Scan Resources
- ☒ Scan Trash
- ☒ Expunge purged items
- Job Frequency: Run Once
- Job Date: 14 Jan 2012
- Time to run job: 00 : 00
- Run job immediately: ☐
- Scan messages in date range: All days
- Scan these users: All Users
- Remove Selected User button
- User input field and Add button
- Scan these folders: All Folders
- Remove Selected Folder button
- Folder input field and Add button

Be sure to finish configuring and enable the job. If the job is not enabled, the POA interface will not be active and mail will not be scanned.

## Vibe Interface Install


The Vibe interface filters all text and attachment workflow through the scanning interface, including input text, all attached files, email, and messaging. To install an interface in the Vibe system, Vibe must be installed and running correctly and the tomcat directory of the Vibe servlet must be known. The Vibe interface may be installed either on the local machine or remotely, similar to a WASP remote interface.

Open the New Interface creation Wizard and select the 'Vibe Interface' option. Click 'Next'.



The screenshot shows the 'Create new Vibe interface' wizard at the 'Welcome' step. The progress bar at the top indicates the sequence: Welcome, Interface settings, Scanner defaults, Confirm selections, Install, and Finished. The main text area contains a welcome message, a note about manual configuration after GWAVA network setup, and prerequisites: 'Have Novell® Vibe installed, configured and running correctly.' and 'Know the location of the tomcat directory for Vibe'. It also mentions a post-install requirement to restart the Vibe application. Navigation buttons '<< Previous' and 'Next >>' are at the bottom.

The wizard states the install process and the required information. Gather the information and select 'Next' when you are ready to install the interface.



The screenshot shows the 'Interface settings' step of the wizard. The progress bar is updated. The form fields are: 'Scanner Name' (Vibe Scanner), 'Install on this server' (gwava6test (Linux)), 'Remote Server Install' (checkbox, currently unchecked), and 'Tomcat Directory' (/opt/novell/teaming/apache-tomcat). A hint for the Tomcat directory is provided: '(e.g. /opt/novell/teaming/apache-tomcat-6.0.18)'. Navigation buttons '<< Previous' and 'Next >>' are at the bottom.


Name the interface and input Tomcat directory serving the Vibe interface.



This screenshot is identical to the previous one, but the 'Remote Server Install' checkbox is now checked, indicating the interface will be installed on a remote server. The text '(Vibe application runs on a server separate from the GWAVA server)' remains.


If the interface is to be installed on a remote server, select the 'Remote Server Install' option and select 'Next'.






Select the scanning options and configuration for the interface. The interface settings may be changed after the interface is created, and defaults show the blocking of viruses and spam.


All other configuration for the interface, including keyword filtering, attachment size, attachment type, fingerprinting, oversize and undersize messages, and specific quarantine settings will all be available for configuration after the interface has been created.



Review settings and select 'install' when they are correct.



Wait for the interface to be installed.



After the Vibe interface has been installed, follow the ending instructions for both local and remote installations. Remote installations will require manual editing of the Tomcat files, as the interface wizard will not have access to them during install. Input the specified lines around the indicated, existing lines in the ssf-ext.properties file, so the file section matches the one shown.

Local and remote installs require a restart of the Tomcat system to restart the tomcat server. Instructions on the restart of Tomcat are provided, select the “?” icon to show the instructions.

Now that the interface has been created, it is available to be further configured and customized.

## WASP Local Interface

To create an interface you must know the correct information for the location of the Web Access directory and the active Tomcat directory. Click **Next**.

(The WebAccess startup file is the webacc.cfg – specify the entire path, including the webacc.cfg filename.)

(The Tomcat directory desired is the one containing the ‘webapps’ directory from which your WebAccess is run. In a standard SLES 10.x system, the path would be: /usr/share/tomcat5. If you have several instances of Tomcat on the same machine, locate the working webapps directory by searching the webacc.cfg file for the “Templates.path=...” line. It will specify the Tomcat path that WebAccess is using. The correct webapps directory will also contain a gw folder - .../webapps/gw.)

It is important to specify the tomcat instance that WebAccess is running on. There may be several instances of Tomcat installed on the same machine at the same time, depending on the way WebAccess was installed.

The screenshot shows the 'Create new WASP interface' wizard at the 'Interface settings' step. The progress bar at the top indicates the sequence: Welcome, Interface settings (current), Scanner defaults, Confirm selections, Install, and Finished. The settings are as follows:

- Scanner Name: WASP Scanner
- Install on this server: gwava6test (Linux)
- Remote Server Install: ☐ (WebAccess Application runs on a server separate from the GWAVA server)
- GroupWise WebAccess startup file: /var/opt/novell/groupwise/webaccess/webacc.cfg  
(e.g. GW7: /opt/novell/groupwise/webaccess/webacc.cfg)  
(e.g. GW8: /var/opt/novell/groupwise/webaccess/webacc.cfg)
- Tomcat Directory: /usr/share/tomcat6  
(e.g. Tomcat 4 on SLES 9/OES: /srv/www/tomcat)  
(e.g. Tomcat 5 on SLES 10: /srv/www/tomcat5)  
(e.g. Tomcat 4 on SLES 10/OES2: /var/opt/novell/tomcat4)  
(e.g. Tomcat 6 on SLES 10/11: /usr/share/tomcat6)

Navigation buttons at the bottom: << Previous and Next >>.

Enter the correct path and name information and click **Next**.

The screenshot shows the 'Create new WASP interface' wizard at the 'Scanner defaults' step. The progress bar at the top indicates the sequence: Welcome, Interface settings, Scanner defaults (current), Confirm selections, Install, and Finished. The content area states: 'You can quickly setup the scanner with some of the most common default security options'. There is a checked checkbox for 'Stop Viruses'. Below it, text explains: 'Enabling virus scanning includes enabling virus sanner services and detecting file types that frequently include viruses with attachment type scanning (i.e. \*.vbs, \*.pif, \*.exe etc) and fingerprinting of attachments.' There is a link for 'advanced settings'. Navigation buttons at the bottom: << Previous and Next >>.

To enable protection from viruses, select “Stop Viruses” to enable the anti-virus engine.

Click **Next**.




The screenshot shows the 'Create new WASP interface' window with the 'Confirm selections' step highlighted in the progress bar. The window contains the following information:

The requisite information has been collected and is ready to be deployed. If you are satisfied that the installation information is correct, press the install button to commit the installation procedure to the GWAVA network.

Scanner name	WASP Scanner
Install to server	gwava6test (Linux)
WebAccess startup file	/var/opt/novell/groupwise/webaccess/webacc.cfg
Tomcat directory	/usr/share/tomcat6
Setup virus scan defaults	Yes

At the bottom, there are two buttons: '<< Previous' and 'Install >>'.

Double check all the information for accuracy, then click **Install** if it is correct. Use the previous button if you need to correct any of the information.




The screenshot shows the 'Create new WASP interface' window with the 'Install' step highlighted in the progress bar. The window displays the following text:

Installing interface, please wait...

This process may take a few minutes. Please be patient and do not change your browser page during this step.

Wait until the next page appears. This may take several minutes depending on the speed of the machine and current load. Please be patient.



This screenshot is identical to the previous one, showing the 'Create new WASP interface' window with the 'Install' step highlighted. It displays the text: 'Installing interface, please wait...' and 'This process may take a few minutes. Please be patient and do not change your browser page during this step.'

Once this page appears, your interface has been successfully created and you can browse away from the interface creation interface.

**NOTE: Your WASP interface will be dormant until Tomcat is restarted and a browser calls the Web Access interface. This is required to initiate the WASP servlet for the web server.** Restart the Tomcat instance you installed WASP to before testing the interface.

WASP 2 interfaces rebrand the WebAccess login and mailbox screens to alert users that WASP 2 is in use. If you do not want this and wish to return to the original branding and artwork, the files were renamed and reside in the following directories:

For GroupWise 7:

<tomcat\_path>/webapps/gw/com/novell/webaccess/images/splash.png

For GroupWise 8:

<tomcat\_path>/webapps/gw/webaccess/<build\_date>/images/install\_watermark\_n.png

WASP 2 has renamed these to \*.bak, (or .bak0 if .bak already exists). Simply rename the file to the original and restart your WebAccess system to return them to default.


### WASP Remote Interface

Running WASP 2 in remote mode means that WASP 2 needs to transfer the mime files via the network to GWAVA in order to be scanned. To create a remote WASP 2 interface, you will need the following information:

The location of the WebAccess configuration file on remote computer (webacc.cfg)


The location of the Functioning WebAccess Tomcat directory – Or IIS directory (The folder containing the ‘webapps’ directory. See notes [above](#).)

Start the interface creation wizard as above, but select the ‘Remote Server Install’ option instead of filling in the paths.




This triggers the remote install mode for the interface.

In remote mode, the installer creates a wasp user and password to connect to GWAVA. The Username is created automatically, but you must specify the password. The user and password will only be used by the wasp interface to connect remotely to the GWAVA server and gain access to the interface. Any password will do. Configure as desired.



Verify all information, and click 'install' when the information is correct. Use the Previous button if you need to change any of the information before you Next.



You **MUST** wait until this page is shown. WASP 2 requires you to copy some files and edit the webacc.cfg on the remote machine for the installation to be successful. If the .jar files are not copied to the locations specified, or the lines supplied are not added to the webacc.cfg, then the remote install will not be able to connect to the GWAVA server and perform scans. **Make sure you copy the supplied lines before browsing away from this page.**

The following page contains instructions that must be followed; the steps must be completed before WASP 2 will function correctly.

The files that need to be downloaded are linked from this page. Create a backup of the current versions of the files you are copying over. Clicking on the name will download the necessary files you need to copy to the locations defined. You must restart Tomcat after the files have been copied over, and the lines added, before the WASP 2 interface will become active.

WASP scanner installation finished

Welcome
Interface settings
Scanner defaults
Confirm selections
Install
**Finished**

Interface installation is now complete.

The GWAVA server is now configured with your new WASP scanner. Because the WebAccess server is running separately from the GWAVA server, you need to complete the following steps on the WebAccess server.

---

**GroupWise® 2012**

Install WASP Application

- Copy the following file to the <tomcat>/webapps/gw/WEB-INF/lib folder:  
wasp2.jar
- On Linux, set the file permissions for that file to "744" and ownership so that it matches the other WebAccess files in that folder.

Configure WASP Application

- Create a folder named "gwava" in the WebAccess Application home folder (this is where the webacc.cfg file is located).
- On Linux, set the permissions for that folder to "755" and ownership so that it matches the "logs" folder in that same location.
- Create a file named "wasp.cfg" in the new gwava folder that contains the following:  

```

Provider.GWAP.class=com.gwava.wa.provider.gwava.GwavaProvider
Provider.Wasp.gwavaman.address=192.168.1.101:49282
Provider.Wasp.gwavaman.username=wsRemote_WAS
Provider.Wasp.gwavaman.password=EA3CA10E7D
Provider.Wasp.reference.id=17gtplq.17h4adu.fj

```
- On Linux, set the permissions for that file to "755" and ownership so that it matches the new "gwava" folder.

Restart WebAccess

- The GroupWise® WebAccess application needs to be restarted for the WASP scanner to become active.

**GroupWise® 8**

Install WASP Application

- Copy the following files to both the <tomcat>/webapps/gw/WEB-INF/lib and <tomcat>/common/lib (if present on Tomcat version 5 and earlier) folders:  
mail.jar, activation.jar
- Copy the following files to the <tomcat>/webapps/gw/WEB-INF/lib folder:  
gwava.jar, wasp.jar
- On Linux, set the file permissions for those files to "744" and ownership so that they match the other WebAccess files in those folders.

Configure WASP Application

- Create a folder named "gwava" in the WebAccess Application home folder (this is where the webacc.cfg file is located).
- On Linux, set the permissions for that folder to "755" and ownership so that it matches the "logs" folder in that same location.
- Create a file named "wasp.cfg" in the new gwava folder that contains the following:  

```

Provider.GWAP.class=com.gwava.wa.provider.gwava.GwavaProvider
Provider.Wasp.gwavaman.address=192.168.1.101:49282
Provider.Wasp.gwavaman.username=wsRemote_WAS
Provider.Wasp.gwavaman.password=EA3CA10E7D
Provider.Wasp.reference.id=17gtplq.17h4adu.fj

```
- On Linux, set the permissions for that file to "755" and ownership so that it matches the new "gwava" folder.
- Rename the file install\_top\_n.png in the <tomcat>/webapps/gw/webaccess/build/images folder to "install\_top\_n.png.bak".
- Copy the file install\_top\_n.png to that folder.

Restart WebAccess

- The GroupWise® WebAccess application needs to be restarted for the WASP scanner to become active.

**GroupWise® 7**

Install WASP Application

- Copy the following files to both the <tomcat>/webapps/gw/WEB-INF/lib and <tomcat>/common/lib (if present on Tomcat version 5 and earlier) folders:  
mail.jar, activation.jar
- Copy the following files to the <tomcat>/webapps/gw/WEB-INF/lib folder:  
gwava.jar, wasp.jar
- On Linux, set the file permissions for those files to "744" and ownership so that they match the other WebAccess files in those folders.

Configure WASP Application

- Edit the WebAccess configuration file (webacc.cfg) on the WebAccess server:
  - Insert a "#" character at the beginning of the line:  
"Provider.GWAP.class=com.novell.webaccess.providers.gwap.XGWAP"
  - Add a new line:  
"Provider.GWAP.class=com.gwava.wa.provider.gwava.GwavaProvider"
  - Add the following lines to the bottom of the file:  

```

Provider.Wasp.gwavaman.address=
Provider.Wasp.gwavaman.username=
Provider.Wasp.gwavaman.password=
Provider.Wasp.reference.id=

```
- Rename the files splash.png and splash-02.png in the <tomcat>/webapps/gw/com/novell/webaccess/images folder to "splash.png.bak" and "splash-02.png.bak"
- Copy the files splash.png and splash-02.gif to that folder.

Restart WebAccess

- The GroupWise® WebAccess application needs to be restarted for the WASP scanner to become active.

---

Click for instructions on how to restart Tomcat which will reload WebAccess.

Note: OES Linux users, [click here](#) to set the proper Linux user and group for your version of Tomcat.

## General Administration


GWAVA administration is completed between two interfaces: the management console, and the QMS management console. The management console runs all administration of the main GWAVA system and interfaces: interface creation, configuration, updates, server settings and management user accounts. The QMS management console contains the administration over the quarantine system: digests, user accounts and login rights, release rights, and Quarantine database size.

## GWAVA Management Console

When you log into the GWAVA Management console, you will view the default user Dashboard. This page displays default gadgets and basic info for your GWAVA system.

The System Status window shows the blocking statistics for your server as well as your evaluation deadline, if you have not licensed your GWAVA system. The statistics window has the option to change the statistics to represent the total, day, last hour, or current hour statistics for each of the shown statistics.


## Dashboards



GWAVA has a user-defined area which opens by default, which can be filled with 'gadgets'. Though there are three default dashboards already defined, the dashboard area was created with the expectation that each system administrator will create and configure their own personal dashboard.




## Dashboard Control Panel



The Dashboard control panel allows for the management of multiple dashboards, and the creation of new dashboards. The dashboard is the default page displayed when users login to the GWAVA Management console. The default dashboard for the homepage is indicated by check mark and little house next to the dashboard name. To change the default dashboard, select the desired dashboard by placing the checkmark in the box next to your choice, and save the changes.


Multiple dashboards may be created or deleted. The current dashboards may be removed, renamed, or reconfigured. The dashboard control panel allows for the creation of new dashboards, renaming or removal of old dashboards, and the selection of the default dashboards.

## Welcome




The Welcome dashboard is the default dashboard for upgrades and new installations of GWAVA, and will be the page seen on first login. The Welcome dashboard has gadgets showing tips, tricks, new information, and links to documentation. The welcome dashboard is not meant to be a permanent default page, but will remain default until changed. As with all dashboards, the welcome dashboard may be configured at any time.

## Status



The status dashboard displays the general status of the GWAVA system; modules reporting working status with the date and time last reported are listed, as well as any alerts and detected viruses. Known viruses will be named, while unspecified or unnamed viruses will remain unnamed. All virus hits are reported.

## Statistics



The statistics dashboard contains basic statistics for the entire system with all interface stats available to be monitored. The statistics vary from total messages processed in the system and breakdowns of different blocked messages to the number of operational threads and system loads according to time of day.

## Configuring and customizing Dashboards

Dashboard pages are essentially blank pages which can be filled with configurable modules called 'gadgets'. Gadgets are gauges, charts, and graphs tied to different statistics and information in the

GWAVA system. Different gadgets display information such as statistics on message flow, system load, detected viruses, blocked connections, RBL hits, and user traffic.


Configuration of any new or existing dashboard is accomplished by adding and removing gadgets to the desired dashboard and configuring the gadget to the desired specifics. Each gadget, after being added to a page, may be moved to any desired location on the dashboard, and the size of the gadget and, or the containing frame.

To add or configure a gadget, open the desired GWAVA dashboard, or create a new dashboard page and select the dropdown tab from the top of the dashboard window to show the gadget selection interface. Clicking on the tab again will either show or hide the gadget selection menu.



Select the desired gadget type and gadget from the dropdown menus and select the add button. The different gadgets may be selected by gadget type, and then desired statistic, or from the desired statistic first, followed by the desired gadget type. Not every gadget type is available for each statistic, as some statistics would not function well in a gauge, graph, or chart form, and is best represented in the forms available.

The currently available gadget types and statistics include the ones shown.



After selecting the gadget desired, some gadgets offer more configuration options, such as time frame, scope of a chart, or the top limit of a gauge. If a gauge offers further configuration, configure the gauges to achieve the desired information needs and select the green plus sign to add the gadget to the dashboard.

Moving gadgets is simple; click and drag the desired gadget to the desired location and orientation in the dashboard window by selecting the top of the containing frame. Different frames may also be sized as desired by selecting the bottom right corner of the desired frame. The mouse pointer will be changed from the system default arrow to a 'move' or a 'resize' arrow. Place and configure the gadgets as desired to create a customized dashboard.

After modifying, moving, adding, removing, or resizing any module, the 'Save Changes' icon must be clicked or the settings will not be saved.

As GWAVA is updated, further gadgets may be added to the GWAVA system.

### Quarantine manager

The Quarantine Manager link opens the Quarantine Manager in a separate browser window or tab. The Quarantine Manager can also be accessed from any browser through the following URL:

[http://<GWAVA\\_server\\_address>:49285](http://<GWAVA_server_address>:49285)

The Quarantine Manager is covered later on in the document. Please see the [Quarantine Manager](#) section.

## **Bookmarks**

The Manage quick access pages link allows the administrator to provide quick access to any page with the bookmark icon in the top right-hand corner. This may shorten browsing times to often visited pages deep in the folder structure of an interface, such as interface statistics or exceptions.

## **Documentation**

Online documentation is linked from the documentation menu, as is the quick install guide, which will not only guide you through basic installation instructions, but will also help in the immediate basic setup for interfaces and management.

## **System Management**


Under the System management link, default settings for the system are listed. The settings here are the base used when creating interfaces. Each interface's settings may be modified individually after interface creation, but by changing the default settings here each interface will be created with the basic default settings correctly.

System Management contains two sections: System management and Advanced. Most work will be completed through the System management section, while the Advanced section contains tools which should be generally left alone unless specified by support.

## System Management

### Licensing

GWAVA must be licensed to use for longer than 30 days and WASP 2 requires a similar license. These licenses may be obtained by contacting the sales representative for your area. Please visit <http://www.gwava.com/company/contact-us.html> to contact your sales representative.



If no licenses are present, the window will state that no licenses have been found. To install a license, select the 'Browse' button and locate the unzipped license file (.pem). After the license file has been located and selected, click the 'Install' button and the license file will be uploaded to the GWAVA server. GWAVA will look for, and recognize the license file in a few minutes. If impatient, restarting GWAVA will trigger the system to look for the license file on startup. Keep an archive copy of the license file for disaster recovery. The license storage location on the GWAVA server is listed at the bottom of the screen.

### Admin accounts

Admin accounts allow you to add and remove administrator accounts from the GWAVA system. These accounts will have full administrator rights to GWAVA Management, as well as default full administrator rights to the Quarantine system.

You may enable or disable four state checkboxes preference from this interface. Four state checkboxes may also be enabled or disabled from any configuration window where the preferences icon is displayed in the top right-hand corner.

### System Information

System information displays exactly that. The Server name, ID, operating system, activation date, address and general status are shown. The status of each of the different running pieces of GWAVA are listed here, along with their latest report-in date, time, and location. This page provides basic information on the system at a glance.

### System Alerts

The System Alerts page displays all the system alerts active, as well as alert history. An Administrator can issue an alert to the system if desired, by selecting the alert and type, then selecting the Send button. Descriptions, severity, source, and solutions may be added to any alert generated from this window.

System Alerts

**Current system alerts**

There are no active system alerts

[Hide alert history](#)

**Alert history**

Resolved	Server	Type	Source	Description	Solution	Reported
Jan 12 06:04:51	SLES11-32 (Linux)	Virus scanner bases are out of date	GWAVA	The virus database is up to date		Jan 12 05:36:19

**Send alert**

Severity	Type	Source	Description	Solution
Notify	License expiration			

## Reports

The Reports function allows the Administrator to setup, send out, or receive regular system reports on the functions and different status of the system. Reports include statistics on:

- Active alerts
- Alerts cleared
- Alerts summary
- Most active recipients
- Most active senders
- Messages processed
- Messages process with a detailed summary
- Most active IP addresses

There are different types of reports based on time frame: daily, weekly, and monthly. Reports are sent to the specified recipients in the list.

Home | GWAVA.com | Support | Help | Logout

Home Pages

- Home dashboard
- Dashboards
- Quarantine manager

Bookmarks

Documentation

System Management

- System management
  - Licensing
  - Administrator accounts
  - System information
  - System alerts
  - Reports**
  - Message tracker
  - Default settings
  - Online updates
  - Package manager
- Advanced

Server / Interface Management

System Reports

Schedule an event to execute

Name	Frequency	Report Time	Day	Recipients
	daily	midnight	0	[Default report recipients]

Report	Format	Type	Report Period	Limit Results
				25


Currently scheduled events

Next Scheduled Time	Name	Frequency	Report Time	Day	Recipients
Jan 12 2012 12:00:00	Daily Report	daily	midnight		[Default report recipients] ✖
Jan 15 2012 12:00:00	Weekly Report	weekly	midnight	Sunday	[Default report recipients] ✖
Feb 01 2012 12:00:00	Monthly Report	monthly	midnight	1	[Default report recipients] ✖






To create and send out a report, specify the name, frequency, and time for the report, and then add the report modules desired to be included in the report.

**System Reports**

**Schedule an event to execute**




Name	Frequency	Report Time	Day	Recipients
	daily	midnight	0	[Default report recipients]

**Report** **Format** **Type** **Report Period** **Limit Results**

    25 

**Currently**

- Active alerts
- Alerts cleared
- Alerts summary
- Most active recipients
- Most active senders
- Most active ip addresses
- Messages processed
- Messages processed detailed summary
- Messages processed full detail summary

Next	Frequency	Report Time	Day	Recipients
 Jan		midnight		[Default report recipients] ❌
 Jan		midnight	Sunday	[Default report recipients] ❌
 Feb 01 2012 12:00:00	Monthly Report	monthly	midnight	1 [Default report recipients] ❌

Add as many or as few report modules to any desired report, but a report should have at least one module to be of worth. Result lists may be limited to a manageable size, and the default is set to 25 items.

Daily Report										Jan 10 2012 12:00:00					
The reports below were generated and e-mailed to you by a GWAVA scheduled event. If you do not want to receive these reports please reply to this email and the administrator can remove you from the recipient list.															
Detailed summary of messages processed between 01/09/12 00:00:00 and 01/10/12 00:00:00															
Total Connections	Inbound	Outbound	Dropped Connections	Client Conversations Terminated	Messages Scanned	Blocked	Quarantined	Recipient Exception	Spam	RBL	SURBL	SPF	IP Reputation	Source Address	
7340	4	0	0	0	7340	2108	1916	0	0	0	0	0	0	80	
Most active senders between 01/09/12 00:00:00 and 01/10/12 00:00:00															
Email Address														Count	
ithaqua@mythos.com														630	
computingresources_support@hotmail.com														626	
photographyschool@hizingawrld.net														282	
cthulhu@mythos.com														259	
e-rios1985@hotmail.com														189	
castrojesse7657@hotmail.com														180	
amy.richardsonspm@hotmail.com														179	

Reports may vary on exactly what is specified to be included and how many items are displayed. The Reports are subject to change and may end up being quite long, yet may be incredibly detailed and helpful in monitoring and managing the mail system.

## Message tracking

GWAVA contains the ability to track all messages which pass through the system, report when they passed and what action was performed on the specified message, and for what reason the action was taken. To access the Message tracker, select 'Message tracker' from the System Management window.

The screenshot shows the GWAVA Message Tracker interface. On the left is a navigation menu with categories: Home Pages, System Management, and Server / Interface Management. Under System Management, 'Message tracker' is highlighted. The main area is titled 'Message Tracker' and contains 'Search Criteria' fields: 'GWAVA message ID' (text input), 'From address' (text input with 'equals' dropdown), 'To address' (text input with 'equals' dropdown), 'Start date/time' (calendar icon with a red X), 'End date/time' (calendar icon with a red X), 'Block state' (dropdown menu set to 'Any'), and 'Max results to return' (text input set to '100'). A 'Submit Search' button is at the bottom.

To track the path of a message through the system, specific information must be known about the message. GWAVA will search through the records to find a message which fits the criteria provided. The tighter the criteria provided, the smaller the results list will be.

Search terms can include:

- GWAVA Message ID
- From and To address
- Timeframe window
- Block state

The GWAVA Message ID is most useful to re-track a message that has been located beforehand, as the message ID's are unique, the result will be the specific message desired. The rest of the criteria is useful to find a message from a specific sender, to a specific user, during a specified timeframe. Setting the Block state search option limits the resulting pool of messages to only those which have either been passed through, or which have been blocked by GWAVA. A search may be performed on one criteria.

Messages that show up in the search may be expanded by clicking on the corresponding

This screenshot shows the same 'Message Tracker' interface but with search results displayed. The 'Search Criteria' section is identical to the previous screenshot, with 'To address' set to 'chris@gwava.com'. Below the search criteria, the 'Search result' section shows a table of results.

Message ID	Timestamp	Message size	Source IP address	Sender	Block state
16b9pmin.1286988123.1i	Wed 13 Oct 2010 11:30:54	652		bot@net.com	none
16b9pmin.1286988123.1m	Wed 13 Oct 2010 11:30:54	597		bot@net.com	none
16b9pmin.1286988123.1k	Wed 13 Oct 2010 11:30:54	918		bot@net.com	none
Block state: none Recipients: chris@gwava.com Message events:					
16b9pmin.1286988123.1o	Wed 13 Oct 2010 11:30:54	1049		bot@net.com	full
Block state: full Recipients: chris@gwava.com Message events: text_filter					



folder to display the pertinent information: all recipients, the block status, and a responsible interface event causing the block.

The full message text is not available in the tracking window. Blocked messages are available to the owner or administrator via QMS. Messages which have not been blocked have been passed to the resident mail system for normal processing.

### **Default settings**

This page displays and allows editing of the default settings used when adding a new server to the GWAVA network. The settings listed here are used to fill out the [Configure Server page](#), which the interfaces read from. It is vitally important that the information supplied for this page is correct for the mail system.

The Administrator email address and name supplied here will appear on all mail notifications and digests sent by the GWAVA system. Any responses to these mail items will be sent to the Administrators address. The Mail relay agent SMTP Server and the QMS SMTP Authentication server are the connection addresses used by GWAVA when sending notifications, digests, and authenticating users for access to their mail in the quarantine system.

### **Online updates**

When a notification that updates are available for the GWAVA system shows on the GWAVA management homepage, this page is where the update is performed. Different update servers may be selected as the source for updated code. The 'beta' server contains unproven code and should not be used on a production system, unless specified by support. The default download servers should be sufficient for most systems.

If the system requires a proxy to access the internet on port 80, then the proxy settings must be provided under the 'Proxy Server Configuration' section under Server/Interface Management | <server name> | Server management | Configure server. There is a link on the update page leading directly to the appropriate page. (The Proxy Server Configuration settings may need to be 'shown' before they are accessible.)

To initiate an update, select the desired update server, and select 'Submit Update Request'. Once an update request has been initiated, GWAVA will contact the update server and begin the download and update process.

### **Package manager**

The Package manager allows the addition of third party and additional plugins to be added and installed to the GWAVA mail system.


To use the Package manager, browse to and select the desired package by using the 'browse' button, then click 'upload' to load the plugin to the GWAVA system. The uploaded package is usually zipped, and the GWAVA system can unzip and install the package.

To unzip, install, or uninstall any third party plugin package use the associated icon under the 'Actions' column. The 'Actions' column will only display the available actions which will identify themselves on mouse-over.

After a package has been unzipped and installed, the GWAVA system may require a restart to initialize the package. See the documentation included with the additional package for details.

## Advanced

The settings in the advanced section of the menu contain categorically organized items for your system. This menu provides scanning configuration identical to the scanning configuration under Server/Interface Management, but differs in that the advanced configuration items are organized by each individual component. It is recommended to use the Server/Interface Management menu for configuration. The advanced section should only be used by support or



under the instruction of support. Items listed under 'Advanced' which are listed under the **Server/Interface Management** section are explained where they reside under the **Interface management** section. The menu items which are separate from the interface tree are found under **System tools**.

## System Tools

System Tools contains powerful tools which modify the core system of a GWAVA server. These tools are not to be used on a regular basis, and should not be used unless instructed to do so by GWAVA support. Editing the database, removing objects and modifying Servers in the GWAVA network may render the GWAVA system inoperative. Only proceed with such operations if you fully understand the process and possible repercussions and on instructions by GWAVA support. The System Tools section will be added to as necessity requires, and new menu items will be self-documented within the system.

## Network, Server & DB Tools

### Replication manager

The replication manager is a tool to push settings found in the current GWAVA system to other servers in a GWAVA network. The connection between two GWAVA servers is created during server activation. Instead of setting up the GWAVA server as a 'new server', select the new server to become part of an existing GWAVA network. If chosen to do so, the manager will assist in replicating the existing configuration database and settings across multiple servers.

### Database Editor

The database editor allows both the viewing and the editing of the GWAVA configuration database. This can be used in coordination with GWAVA support. Do not use the database editor without explicit instruction and aid from GWAVA support.

The editor prompts you to spawn a new window and then offers the option to open the selected table in either viewing only, (default setting), or in the editing mode, which allows changes to be committed to

the database. The editor also includes a search function which passes queries to the database and allows the response to be limited to a desired level of results. Changes to the database in the editor are immediate. To exit the editor, simply close the window.

### ***Server Maintenance***

Standard core functions for GWAVA maintenance are listed here. Removing and renaming a GWAVA server from the GWAVA networks correctly severs or renames a connection between two GWAVA servers. Removing a connected server from a network should be done prior to uninstalling the GWAVA server in order to avoid connection issues with the remaining GWAVA server(s).


Due to updates and changes in the GWAVA interface, it may be necessary to rebuild the system Menu's. Selecting this option causes the GWAVA system to discard the current menu tree and system in the GWAVA interface, and recreated them from the current system files. If a new item has been installed or downloaded to the GWAVA system during an update and a menu rebuild is appropriate, you will be notified on the default GWAVA home page, under the system status window. The notice will be a link which initiates a menu rebuild. Utilization of this option under the system tools should not be necessary under normal operation.

### ***Database Migration***

The Database Migration tool migrates the internal SQLite database to an external Postgres database. Migration is a relatively simple process which is automated by GWAVA, however, database migration may take some time, and may take quite a long time depending on the size of the internal database. During database migration GWAVA services and scanning will be unavailable.

All maintenance, installation, tuning, and administration of the Postgres system is the responsibility of the system administrator. GWAVA offers no technical support for third party programs.

The Database Migration itself has detailed instructions in place. Read all of them before proceeding with the database migration. The migration process consists of several steps and pre-requisites which must be completed before continuing. Once all steps are completed, the migration can continue.



Shutting down all peripheral programs to gwava, except the 'gwavaman' process will leave the administration interface functional and accessible for the migration process. **It is critical that all peripheral GWAVA process be shut down before the migration is started.**

The migration itself may take quite some time depending on the size of the SQLite database, and during this time GWAVA will not scan mail and messages will not be passed through the system.

Enter the connection information to a pre-created, blank, PostgreSQL database, and select the 'Start Migration' button to begin the migration. Once the migration has been completed, the peripheral GWAVA processes need to be started to initiate the quarantine and statistics data migrations. Once those have completed, the entire GWAVA system needs to be restarted in order to complete the migration. Once restarted, GWAVA will be functioning from the PostgreSQL database.

Database migration

GWAVA 6 Database Migration Wizard

Once you have prepared your PostgreSQL database, follow the steps below to transition your GWAVA system.

Installation Steps

- Shut down GWAVA peripheral programs, leaving only GWAVAMAN running
- Provide your PostgreSQL database connection information
- Wait for the GWAVAMAN database to be migrated
- Restart GWAVA peripheral programs
- Wait for quarantine and statistics data to complete migration
- Restart all GWAVA programs

Postgres connection parameters

Please provide the connection details for the PostgreSQL server to be migrated to

Postgres host server

localhost

Postgres database name

GWAVA

Postgres login name

Postgres login password

Start Migration >>

### ***Diagnostics & Repair***

The diagnostics section of the GWAVA management interface is designed for troubleshooting use and works in conjunction with the base components of the system. These tools should not be played with or used without full understanding of the effects. Use of these tools without the guidance of support may cause serious issues with the GWAVA system and network.

### **Server/Interface Management**

The Server/Interface Management is setup in a directory tree-view organized around tasks. The Server management offers active setup information on the GWAVA server. The Wizards menu contains all interface creation options. The Manage interfaces menu contains all currently active and created interfaces and their configuration options.

### **Server management**

This menu contains all of the active settings in the GWAVA system for the GWAVA server. Editing and saving changes in this section changes the active settings in the GWAVA server within a couple of minutes.

### ***Server status***

The Server status page displays the basic status and rundown of the server and the platform it detects as the running system. The server name, up time, server time, database ID, object, and record count, thread count, and replicator status and queue are listed.

### ***Configure Server***

In the Configure server window, all of the connection settings for the server are listed as well as the log level, statistics, and reporting settings. The administrator address and name configured on this page will be used for alerts.

The Admin name and address is the default source address for digests and notification messages sent by GWAVA to users in the system. If replied to, the messages will return to the address listed here.

The QMS authentication server should be the connection to the GWIA for GroupWise systems, in order to allow user-level access to the quarantine manager for each user's respective quarantined mail.

Configure Server	
▼ General	
GWAVAMAN root directory	/opt/beginfinite/gwava/
Administrator e-mail address	admin@gwava.com
Administrator full name	administrator
Log level	Normal ▼
Keep log files for (days)	7
Enable auto restart on agent failure	<input checked="" type="checkbox"/>
▼ QMS configuration	
Enable QMS data pruning	<input type="checkbox"/>
Days to retain messages in QMS	
Prune stored messages	<input type="checkbox"/>
Prune database entries	<input type="checkbox"/>
Backup and maintenance time	00:00 ▼
▼ SMTP relay configuration	
SMTP relay agent target server	192.168.1.120
Force outbound mail to relay target	<input type="checkbox"/>
Mail relay SMTP auth login	chris
Mail relay SMTP auth password	••••••••
▼ Reporting and alert configuration	
E-mail alerts	<input checked="" type="checkbox"/>
Alert recipients	
Default report recipients	

If your GWIA requires a special greeting, or authentication type, or you use an external SMTP server which requires special authentication or login information, this is where GWAVA is informed of the connection. For most systems, the only configuration performed on this page is the “Maximum SMTP send threads” variable. This determines the maximum amount of threads which GWAVA will use to send notification or digest messages to the GWIA or receiving SMTP gateway in the mail system. This should be less than the total number of receive threads open on the GWIA or the SMTP agent, to ensure that the mail system is not overwhelmed when digests are sent.

▼ Advanced QMS configuration	
QMS role	Master ▼
QMS parent server (when in slave mode)	[none] ▼
[custom] QMS master address	
[custom] QMS master login name	
[custom] QMS master password	
QMS queue directory (relative to root)	services/qms/in_queue
Enable QMS nightly backup	<input checked="" type="checkbox"/>
Enable QMS nightly reindex	<input type="checkbox"/>
Enable QMS nightly vacuum	<input type="checkbox"/>
Enable QMS integrity checks	<input type="checkbox"/>
QMS database size warning threshold (in megabytes)	2000

The Advanced QMS Settings allow the function of newer QMS tools to help clean and maintain the qms database. The nightly backup and integrity checks do exactly as they say. The database vacuum and reindex services clean out bad links and files, and reindex the files in the database for faster searching. The database vacuum and reindex services normally do not need to be used, and should only be triggered under the direction of support.

The QMS role is an option to allow all QMS data to be stored in a central location when utilizing multiple GWAVA servers in a system. The 'Master' role sets QMS to have all quarantine data copied to that server from 'Slave' QMS servers. Slave QMS servers will contact the Master QMS and copy all quarantined data and messages to the master, storing all quarantined messages in a central location. This should not be changed unless multiple GWAVA servers exist in the system.

### Advanced Statistics settings

Settings enabling the collection and governing the statistics engine in GWAVA are set here. Defaults are shown. If records of statistics are to be kept, backup of, as well as retention time of statistics should be set as desired. Be careful not to retain stats for a long period, as busy systems can quickly amass very large statistics databases.

Additional statistics configuration	
Enable statistics	<input checked="" type="checkbox"/>
Statistics queue directory (relative to root)	<input type="text" value="services/stats/in_queue"/>
Days to retain statistics	<input type="text" value="30"/>
Prune information from statistics database	<input checked="" type="checkbox"/>
Statistics database maintenance time	<input type="text" value="02:00"/>
Enable statistics database nightly backup	<input checked="" type="checkbox"/>
Enable statistics nightly reindex	<input type="checkbox"/>
Enable statistics nightly database vacuum	<input type="checkbox"/>
Enable statistics nightly database analyze	<input checked="" type="checkbox"/>
Enable statistics database integrity check	<input type="checkbox"/>
Statistics database size warning threshold (in megabytes)	<input type="text" value="2000"/>
Statistics batch processing buffer size	<input type="text" value="1 Mb"/>
Statistics role	<input type="text" value="Master"/>
Statistics parent server (when in slave mode)	<input type="text" value="[none]"/>
[custom] Statistics master address	<input type="text"/>
[custom] Statistics master login name	<input type="text"/>
[custom] Statistics master password	<input type="text"/>

## Advanced SMTP Relay Configuration

If additional SMTP settings are required to allow an SMTP relay to function correctly, the settings are located here. Limitations on sending threads and retry intervals as well as authentication methods can be configured to suit the requirements of the host system.

▼ Advanced SMTP relay configuration	
SMTP outbound queue directory	<input type="text" value="services/smtp_mailer/outbound"/>
Mail relay SMTP greeting	<input type="text"/>
Mail relay authentication method	<input type="text" value="Auto-detect"/>
Mail relay maximum send threads	<input type="text" value="16"/>
Mail relay retry interval	<input type="text" value="15"/>
Mail relay retry maximum count	<input type="text" value="16"/>

## Proxy Configuration

If your system accesses the internet through a proxy, add the information here using the syntax proxy.myfirewall.com:8080. If a proxy is not used, this should be let blank.

▼ Proxy configuration	
Use proxy server	<input type="checkbox"/>
Proxy server address	<input type="text"/>
Proxy server login	<input type="text"/>
Proxy server password	<input type="text"/>

## IP Configuration

The connection addresses for the different objects in GWAVA are listed and configured on this page. *There is no reason to configure these settings on standard GWAVA installations unless the GWAVA server has been installed to a cluster.* These settings should not be changed unless instructed by GWAVA support.

▼ IP configuration	
GWAVAMAN server address	<input type="text" value="192.168.1.148:49282"/>
GWAVAMAN Listen address (IP[:port])	<input type="text" value="0.0.0.0"/>
GWAVAMAN enable SSL	<input type="checkbox"/>
GWAVAMAN SSL listen address (IP[:port])	<input type="text"/>
QMS listen address (IP[:port])	<input type="text" value="0.0.0.0"/>
QMS enable SSL	<input type="checkbox"/>
QMS listen address SSL (IP[:port])	<input type="text"/>
GWAVA listen address (IP[:port])	<input type="text" value="0.0.0.0"/>
STATS listen address (IP[:port])	<input type="text" value="0.0.0.0"/>
GWVRELAY SMTP source bind address	<input type="text"/>



## SSL

SSL configuration is offered under the 'SSL Configuration' section at the bottom of the page. If the system requires SSL for security or for integration into an existing system, ensure that all the required information is prepared for the server.

▼ SSL configuration	
SSL certificate file	<input type="text"/>
SSL key file	<input type="text"/>
SSL key password	<input type="text"/>
SSL version 3 required	<input type="checkbox"/>

## Advanced


If it is required to ignore the .com fingerprint in body of the message text, this option may be set here. Messages containing references to domains or link types, but which are not from those domains, may be blocked due to the links. If this is a problem, it may be disabled.

▼ Advanced	
Skip .com fingerprint in text body	<input type="checkbox"/>

## Configure Domains

All domains for which the host mail systems receive mail must be listed on this page, as either the default domain or as an additional domain; otherwise, GWAVA will not accept mail sent to a domain(s) not listed. This section is covered under the [SMTP interface creation section](#).


## Server control




The GWAVA server functions can be controlled from this section; stopping or restarting GWAVA and mail flow. This is useful if there is a need to pause the mail flow in the system or if GWAVA needs to be restarted or worked on.

## Antivirus agent setup

GWAVA comes with the Antivirus engine automatically setup and active. This page gives information on the Antivirus agent. The antivirus will connect to the internet and download virus updates hourly, therefore the antivirus only needs to be configured if the network utilizes a proxy to access the internet. (Proxy server settings are specified during server activation, and may be added or configured later on the **Server/Interface Management | <Server name> | Configure Server** page under the **Proxy Server Configuration** section.)



## IP Reputation Setup



**Note:** Changes to these settings may require GWAVA on server SLES11-32 (Linux) to be restarted to take effect

Signature spam connection address	127.0.0.1
IP reputation service connection address	127.0.0.1

The GWAVA scanning system can provide signature and IP reputation services to other GWAVA servers in the same network. If a secondary GWAVA server is to provide the interface service, the connection information for that server must be specified via IP address. The default configuration is to have the local host provide the scanning service.

## Logs

GWAVA keeps logs for each major module in operation, with the logging level determined by the server configuration. For most situations, leaving the log level at normal will be sufficient. The Log menu option allows the admin to view the logs from the GWAVA management console. The logs are also available in the file structure for offline viewing. The file location is listed at the top of the log page.

<Where gwava is installed>/gwava/services/logs/<module>/<log>



The left pane shows a directory tree for GWAVAUPD, including subdirectories like asengine, autoblocker, gwava, gwavaman, gwavapoa, gwavaqms, gwvgwia, gwvrelay, and gwvsmtp. The file 20090414.log (5756 bytes) is selected under gwava.

The right pane displays the content of the log file: /opt/beginfinite/gwava/services/logs/gwava/20090414.log. The log shows various system events and client connections/disconnections.

```
Displaying log file: /opt/beginfinite/gwava/services/logs/gwava/20090414.log

[2rrgdlg][2] APR-14 09:15:38 Init: gwava version 4.00 release build 99
[2rrgat0][2] APR-14 09:16:26 Configuration notification handler started
[2rbg2t0][2] APR-14 09:16:26 Starting client listener process on interface 0.0.0.0
[2r3fut0][2] APR-14 09:16:26 Client connected from 127.0.0.1
[2qrfqt0][2] APR-14 09:16:27 Client connected from 127.0.0.1
[2q3fet0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2prfat0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2pjf6t0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2pbf2t0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2p3eut0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2oreqt0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2ojemt0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2obeit0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2o3eet0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2nreat0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2nje6t0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2nbe2t0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2n3dut0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2mrdqt0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2mjdnt0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2mbdit0][2] APR-14 09:16:28 Client connected from 127.0.0.1
[2qrfqt0][2] APR-14 09:43:13 Client disconnected
[2mbdit0][2] APR-14 09:43:13 Client disconnected
[2mjdnt0][2] APR-14 09:43:15 Client disconnected
[2n3dut0][2] APR-14 09:43:17 Client disconnected
[2r3fut0][2] APR-14 09:43:18 Client disconnected
```

The different modules perform different tasks. The main modules to view, if desired, are:

- gwava – the main interface
- gwavapoa – post office interface
- gwavaman – management
- gwavaqms – quarantine manager
- gwvsmtp – GWAVA Smtip service

## Wizards

This feature is covered under the [interface creation](#) section.

## Manage interfaces

The Manage Interfaces menu option contains the settings for each interface, organized under each interface's name. To bulk modify interfaces, the interfaces must share an interface engine. See the '[Advanced](#)' section for more information.



## Interface settings

This menu item lists the basic connection and interface settings for the different interfaces specified during each interface's creation setup wizard. Each interface type will have a different interface setting page with only the information that each interface deals with. For instance, a GWIA interface's interface page only lists the home directory and mail flow settings, as that is all which is required to interface with a functioning GroupWise Internet Agent.

Scan inbound mail	<input checked="" type="checkbox"/>
Scan outbound mail	<input checked="" type="checkbox"/>
GWIA home directory	/mail/dom/wpgate/gwia
Maximum scan threads	16

The following is a SMTP interface, which requires a binding TCP/IP listening address, and any other connection settings, depending on your network setup.

Scan inbound mail	<input checked="" type="checkbox"/>
Scan outbound mail	<input checked="" type="checkbox"/>
TCP/IP bind address (listen address)	192.168.1.104
Client thread timeout	300 (seconds)
Maximum number of threads	32

**Note:** Changes to the TCP/IP bind addresses require the GWVSMTP program to be restarted to ensure they take effect

Hosted Domains : [Edit address\(Additional internet domains\)](#)

Trusted outbound relay servers


127.0.0.1
192.168.*.*
172.16.*.*
10.*.*.*

[Remove Address](#)

[Add Server](#)

[Show optional SMTP settings](#)

## Interface Uninstall




When you select the uninstall option you are prompted to confirm that you wish to remove the entire interface. Be aware, there is no restore option for uninstalled interfaces. Uninstallation does not remove abilities or associated policies from the system, but it does remove the interface from the selected options in those policies and configurations.

## Scanner / Policy Management

### Policy Manager


GWAVA introduces the 'policy' to the GWAVA interface. Policies are utilized mainly for multi-tenant systems; systems with multiple domains, interfaces, or both. GWAVA and the Policy Manager disassociate domain settings from the interface, allowing multiple managed domains under the same interface, or vice versa. If, for example, multiple domains are hosted on a large system with load balanced SMTP servers, the policy manager can implement several different scanning profiles through a single or multiple SMTP interfaces all controlled by the same GWAVA server. A policy may also be used to manage several completely separate domains hosted on the same SMTP server, through the same SMTP scanning interface, with different criteria for each domain.



By Default, the Policy Manager automatically creates and manages policies for interfaces. Unlocking the Policy Manager permanently disables automatic management. If the GWAVA system is setup to only utilize a single domain and interface, or the different domains managed are to have the same scanning policy, then the Policy Manager should be left to manage the policy automatically. Policies are required for scanning to be completed, as they are the framework for all mail flow and dictate what mail 'qualifies' for scanning.

The active policy can be viewed at any given time, but once the policy manager is unlocked, or opened in editing mode, the GWAVA system will no longer automatically manage the policy. This means that every


time an additional interface is added to the system manual manipulation of policies is required. The simplest way to deal with the Policy Manager is to allow the Policy Manager to be automatically managed by the system.



Viewing policies in read-only mode displays all the pertinent information in a grayed-out text. Selecting the different parts of the existing policy tree will display the policy active on each section.

Every automatically created and configured policy contains identifying notes, and will be tied to the interface that it was created with.

All gray text and settings are locked and cannot be modified.



One of the most useful ways to use the read-only Policy Manager is to check active direction scanning settings. If mail is unintentionally being caught on outbound scanning, it can become a difficult situation to detect or understand. The Policy Manager can quickly display which scanning directions qualify for scanning with the system in question simply by selecting the desired policy and checking the scanning direction settings. With a policy, a selected option restricts the filters, limiting only mail qualifying with the selected options to be scanned.

The different settings are as follows:

Match message direction – restricts direction scanning


Inbound – Scans inbound messages

Outbound – Scans outbound messages

Internal – Messages with destinations within the system.

Collected – Scans messages which are being stored in the system

Composed – Scans “draft” messages which have been created, but not sent




In the displayed example, only inbound mail will be scanned according to this policy. Outbound, internal, collected, and composed mail will be exempted from the policy. If, however, the message direction option is left unchecked, then all directions will be scanned according to the rest of the policy.

How mail qualifies for scanning is described in the [‘How mail flows through a policy tree; Qualification’](#) section below.

Any automatically created policies with previously created scanners will be displayed as root-level policies with their own scanning configurations.


If multiple interfaces are configured on creation to share a policy, only the one policy will be shown, but it will be connected to both interfaces. All scanning configuration may be edited or changed under the Scanner/Policy Management menu tree.

For scanning settings, please see the next section, [Scanner / Policy Management](#), where all scanner settings, configuration, exceptions, and message services are configured.




## Unlocking the Policy Manager

To unlock the policy manager for direct editing, the administrator must verify that they understand that they are disabling the automatic management.




Select the checkbox then click the 'Unlock Policy Manager' button.



Once the Policy Manager has been unlocked, select the blue link to continue. This page and warning will not be displayed again.

When unlocked, the policy tree has an additional drop-down menu to enable editing of the tree, called 'Policy tree editor'.






Opening the Policy tree editor exposes a checkbox as well as an additional drop menu explaining all of the editing icons.


When the checkbox is selected to enable editing of the policy tree, the editing icons are displayed on each policy as shown.

To create a new policy under, below, or next to an existing policy, enable the policy tree



editor and then find the desired parent policy. Select the appropriate icon and complete the wizard displayed in the


information window. The wizard is a standard policy creation wizard and is nearly identical to the interface creation wizard. Upon wizard completion, the new policy is created.



To move a policy, enable the policy tree editor and select the scissors, (cut), icon on the policy that is to be moved. Then find the policy that is to be the parent or neighbor to the newly 'cut' policy and select the clipboard, (paste), icon. After the paste icon has been selected, locate the appropriate arrow designating the new location for the policy. All arrows are relative to the location of the 'paste' selected policy; left of, right of, sub policy, or parent of

the selected policy.


Policies may also be created at the root of the policy tree without selecting the tree editor. Simply select the 'Policy Definitions' button at the top of the tree then select the 'Create root level policy' button in the information window. This will spawn the policy creation wizard. Completing the wizard will create a root level policy.



## How Mail flows through a policy tree; Qualification

Mail flowing through the GWAVA system must 'qualify' for specified criteria before it can be scanned by the policy. Any mail that does not qualify for the policies defined will simply pass through the system untouched and unmodified. Due to this qualification, any system with multiple domains must not only add those domains to the configure domains page, but each domain must either have a policy connected to it, or must qualify for a general policy in order for that domain's mail to be scanned. The qualifications will be covered with the example below.

The policy tree dictates how mail will flow through the system, and is useful for Multi-tenancy setup and control regardless of how many interfaces the policies are tied to. The following system has been setup to show some complexity available for system mail flow and to explain the system.



## Multi-Tenancy and Policy Trees

In the example, five different domains are active and hosted on the same SMTP server: GWAVA.com, beginfinite.com, hostedinc.com, corpx.com, and corpy.com. The different domains require different scanning settings and message services. GWAVA.com mail is scanned differently from the beginfinite.com messages. In addition, a hosting company is also present which manages two domains for customer organizations that require their own scanning configurations. In addition, the general settings for the gwava.com domain are insufficient for both the sales and the support users, which have different requirements for message services. With policies created for each of them, all their scanning and message service requirements can be fulfilled.

This configuration is tied to domains, message direction, and sender addresses and all contain a scanner. It is important to assign policies to contain a scanner; otherwise the policy will not scan the mail.

(In the event that a message is sent to multiple recipients matching several or all of the different domains, the message will be 'split' and copies scanned according to each individual policy, then sent to their respective recipient(s) in each domain.)

When messages come to the GWAVA system through an interface, the GWAVA system compares the mail to the policy tree to find any policy that the mail qualifies to be scanned by. All of the qualifying criteria are displayed in the information window. (Mail flow is explained in more detail on the next page.)

Criteria selected in the qualification window limits the amount of mail that the policy may match. The more active criteria enabled on a policy, the harder it is for mail to qualify.

The displayed policy only requires that mail be sent to the gwava.com domain to qualify for the scanner. With this configuration, only mail that is sent to the gwava.com domain will be scanned by the GWAVA Inc. policy.

With the above example, the Hosted Inc. organization is hosting not only their own, but two additional domains which they manage and provide base service to in addition to specific services for each domain. To provide that service, the Hosted Inc. policy must contain bindings to all three domains. The messages will then be moved further down the tree to the sub-policies that also apply to their respective domains for Corp X and Corp Y, with their specific scanning criteria.

For example, messages sent to Corp X will be scanned according to the Hosted Inc. policy and then the additional Corp X policy as well.

Policies which appear underneath another policy, sub policies, automatically inherit the scanning limitations of the parent policy as mail moves through that configuration first.

See the Hierarchy section in the [appendix](#) for more information.

Because sub policies are subject to the parent policy, when specific configuration of the scanning engine is performed, the sub-policies are found nested underneath their parent.

Sub-policy scanning configuration contains all the same settings that a parent scanner contains, and can be configured independently. When configuring nested policies for scanning, it is wise to ensure that the parent scanner does not contain any unwanted scanning configuration to minimize conflicts which could disrupt mail flow.

**Policy Qualifications**

The rules defined here determine whether a message will be scanned by this policy. Your scanning configuration (whether a message is blocked, quarantined etc) is separate from its policy and is configured in the Scanner Management panel to the left of the management console.

Policy name: GWAVA Inc.

Notes:

- ☒ Policy contains scanner
- ☒ Policy can backtrack
- ☐ Match message direction
- ☐ Match recipient address
- ☐ Match sender address
- ☐ Match any address
- ☐ Match recipient domain
- ☐ Match sender domain
- ☒ Match any domain
  - ☒ gwava.com
  - ☐ beginfinite.com
  - ☐ hostinginc.com
  - ☐ corpx.com
  - ☐ corpy.com
- ☐ Match message size
- ☐ Match ip address
- ☐ Limit to servers
- ☐ Limit to interfaces
- ☐ Limit interface type

Match any domain ☒

- ☐ gwava.com
- ☐ beginfinite.com
- ☒ hostinginc.com
- ☒ corpx.com
- ☒ corpy.com

**Scanner / Policy Management**

- Policy manager**
  - GWAVA Inc.
  - beginfinite.com
  - Hosted Inc.
    - General settings
    - Scanning configuration
    - Message services
    - Exceptions
    - Corp X
      - General settings
      - Scanning configuration
      - Message services
      - Exceptions
    - Corp Y

## Specific Policy Settings


### *Policy contains scanner*

The 'policy contains scanner' setting is useful in complex configurations, but can be useful for some standard configurations as well.

The policy management structure allows mail to be categorized as it flows into the mail system and scanned according to each category the messages 'qualify' for. Examples of different possible categories include: inbound and outbound mail, sales and marketing departments, technical and executive mail, or students and teachers. Each of these categories can be clearly defined by the receiving users and each group has different scanning needs. The 'policy contains scanner' setting becomes very useful and necessary when managing increasingly complex settings including multiple sets of categories and users in a policy tree.

In an example of such a complex policy tree, we'll use a single organization containing three very different departments. A simple setup would contain a policy for each department, which functions wonderfully until each department also has its own sales, management, marketing, and technical staff requiring different scanning rules to accommodate mail needs. It is important to correctly setup a policy tree when dealing with complex configuration to maintain a simple, and easy to read, setup.

In understanding how to create complex scanning configurations, it is helpful to create organizational policies, or 'container policies'. Container policies are organizational categories and do no scanning of their own, but are placeholders or containers to meaningfully organize the policy tree.



The different departments shown above are containers for the different organizations and scanning policies. In the above layout, scanner settings are configured and independently implemented for each department within the organization, and it is easy to visually identify the structure and layout of the GWAVA scanner.


Keep in mind that this layout represents which scanner configurations will be used to inspect messages does not necessarily reference or depend on the server or MTA that messages are passing through. Referencing the diagram, this layout would be well suited for an IT department that has a single SMTP the mail comes into. Even though the mail is all passing through the same entry point, GWAVA will pass every message through the policy manager to be sorted, categorized, and scanned according to the

policy that the messages qualify for. A message that comes for a sales representative from the clothing branch will be scanned by the rules for his organization, and none of the others.

### Backtracking and Mail Flow

Backtracking is mainly used with complex policy structures. In most systems the backtrack option should be left enabled. To correctly explain backtracking it is necessary to look at mail flow in slightly more detail.

Backtracking is related to the way in which mail 'walks' the policy tree looking for a qualifying policy, or the correct scanner, to use for any particular piece of mail. The comparison movement is top to bottom, left to right. This process is shown below, where a message for a 'Staff' member of the 'Restaurants' department is sent mail. When their messages are received they will systematically walk the tree in the following manner.



With this defined path for mail in a policy system, it is easy to see what will happen with mail. Messages are passed and compared to every policy in a system, and scanned and released appropriately.


If a message does not qualify for any of the policies then ends up without a policy at all and will pass through the system without being scanned. This ability is useful for only scanning a portion of mail for a particular set of users. An example where disabling backtracking would be useful is when the system is required to scan the mail in the clothing department for the sales, management and marketing but no one else.

If all messages are to be scanned, a default or generic scanner policy can be created to scan all messages which do not qualify for any other policy. This ensures that all mail is scanned. As shown below, the policy has been modified to include a default, generic policy.

Backtracking becomes effective when all mail that is not for a specific department that is managed should be scanned by the default scanner, but messages within a department that have not been targeted for scanning should be ignored.

The policy tree shown below shows a situation where a message might have been received for someone in the IT department. The IT department requires that their mail is not scanned. As the message passes down the tree, it does not pass into the 'Furniture' container because it does not qualify (likely by a domain qualification), then moves on to the Clothing container, which it qualifies for at a high level (again, likely the domain '\*@\*clothing.company.com'). At this point the message passes over all of the child policies looking for a match for the message, but it does not qualify for any other policy.

At this point, the backtracking feature kicks in. Normally, the next step for the mail is to go back up to the 'Clothing' policy and move right, but the message hits the 'no backtrack' option at the root policy and graduates from the policy tree without completing the tree walk. The result of this is that the IT department's mail bypasses scanning, as it is prevented from continuing to the final destination of the 'Default' policy by disabling backtracking.




Backtracking is a feature that is normally wanted for the very purpose of falling back to a default scanner, however when you come across a need to stop a specific type of mail from being scanned, backtracking provides that ability.

## Scanner Management

Scanning configuration is organized under each respective policy name, which governs what messages are scanned. Root policies are listed by themselves, while sub policies are nested within the parent configurations.

## General Settings



**General configuration**

Enable services

Enable scanner services	<input checked="" type="checkbox"/>
Enable outbound scanning	<input checked="" type="checkbox"/>
Enable inbound scanning	<input checked="" type="checkbox"/>
Enable collected item scanning	<input checked="" type="checkbox"/>


Enable Scanner services: Enables the interface, or places the interface in bypass mode.

Enable outbound scanning: Enables the interface to filter outbound mail.

Enable inbound Scanning: Enables the interface to filter inbound mail.


Enable collected item scanning (POA): Enables the POA interface to function if attached.

The defaults for the Scan direction settings are shown. The Per event scan direction settings perform the same as the global settings described above, except that it only applies to specific interface events. The default is shown, with all enabled except outbound Anti-spam scanning. In example: if SURBL, RBL, IP reputation or SPF are enabled on the interface, but are not desired for outbound mail, unselect the scan outbound box for those services and click the save changes button to apply them in the interface. The 'Scan Collected' box ONLY applies to scanning a GroupWise Post Office, and will only be useful if the interface being modified is a POA interface.



Scanner event	Scan inbound	Scan outbound	Scan collected
Virus scan	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Antispam heuristics	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
RBL	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SURBL	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
IP reputation	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SPF	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Text filtering	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Raw MIME filter	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Header filter	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Oversize	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Fingerprint	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Attachment type	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Source address	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Destination address	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
IP address	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Image analyzer	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

General Settings govern the notification address and settings for the selected interface. The general settings are taken from the system default settings, and do not need to be set or changed unless a different notification address from the default is desired for different interfaces.



**General settings**

Administrator e-mail address	<input type="text" value="bitter@gwava.com"/>
Administrator full name	<input type="text" value="bitter"/>
Use message date field for quarantine timestamp	<input type="checkbox"/>

The Advanced Decompression Settings dictate how deep a message is scanned. Default recursion is 4, and all options are selected.

▼ Decompression settings	
Enable decompression services	<input checked="" type="checkbox"/>
Maximum Recursion Depth	<input type="text" value="4"/>
Scan Archive shell	<input checked="" type="checkbox"/>
Decompress EXEs	<input checked="" type="checkbox"/>


Advanced System Settings provides customization on the timed delay. This delay is the amount of time that GWAVA waits to reload system configuration after a change has been made in the management console. Default is 30 seconds for a change delay, and the max delay is set to 60 seconds.

▼ Advanced settings	
Settings change timed delay (seconds)	<input type="text" value="30"/>
Settings change max delay (seconds)	<input type="text" value="60"/>
Generate diagnostic CF files with PCR files	<input type="checkbox"/>

By default, GWAVA will not generate a diagnostic CF file with the scanning PCR files. These files are temporary files used when troubleshooting the message scanning process. Unless specified by support, there is no need to create a CF file.



## Notification



The Notification configuration window contains the following sections:

- Template files**

Administrator notification template	notify_admin.shtml
Originator notification template	notify_originator.shtml
Recipient notification template	notify_recipient.shtml
Defined addresses notification template	notify_generic.shtml
- Notification direction limit**

	Inbound	Outbound
Notify sender	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Notify recipient	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Notify administrator	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Notify defined address(es)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
- Advanced notification settings**



Notification from name	<input type="text"/>
Notification from e-mail address	<input type="text"/>
Use custom logo in notifications	<input type="checkbox"/>
Custom logo relative path	<input type="text"/>

The notification options allow you to specify which templates are used to create the message, the send from address, (the admin address and name are the default used as the 'From:' address), and the events specified for notification. Events specified for notification here still depend on the notification setting to be active in the individual interface events.

## Scanning configuration

### Antivirus

The default antivirus scanning settings are set to scan messages for viruses, and if a virus is found, the message is immediately blocked/deleted, and, regardless of any other setting in the system, never added to the quarantine. See the [four state checkbox](#) section in the appendix for details.



The Antivirus configuration window contains the following sections:

- Scan configuration**


Enable virus scan	<input checked="" type="checkbox"/>
-------------------	-------------------------------------
- Scan result actions**

Block the message	<input checked="" type="checkbox"/>
Quarantine the message	<input type="checkbox"/>
Notify the sender	<input type="checkbox"/>
Notify the recipient(s)	<input type="checkbox"/>
Notify the administrator	<input type="checkbox"/>
Notify defined address(es)	<input type="checkbox"/>

## Antispam

### Spam Detection

Spam detection is performed against the signature scanning engine. Messages detected as spam by the system will have the following selected actions performed on them. Spam messages are not required to be blocked or sent to quarantine, they can simply be flagged and sent along, or flagged and have their subject re-written. However, the default action is to block and quarantine to keep mailboxes free.




The screenshot shows the 'Spam detection' configuration window. It has a title bar with standard icons. The window is divided into several sections, each with a green arrow icon and a title:

- Scan configuration**
  - Enable spam detection: ☒
- Confirmed spam actions**
  - Block the message: ☒
  - Quarantine the message: ☒
  - Flag the message as junk: ☐
  - Rewrite the message subject: ☐
  - Subject rewrite template:
- Bulk spam actions**
  - Block the message: ☒
  - Quarantine the message: ☒
  - Flag the message as junk: ☐
  - Rewrite the message subject: ☐
  - Subject rewrite template:
- Valid bulk mail actions**
  - Block the message: ☐
  - Quarantine the message: ☐
  - Flag the message as junk: ☐
  - Rewrite the message subject: ☐
  - Subject rewrite template:

### SURBL

The SURBL event checks each message against the SURBL databases listed in the SURBL servers listed, to see if the sending server is included on the SURBL list. If it is included, the message is blocked. SURBL servers may be added or removed from the active list as desired. (It is not recommended to have more than two SURBL servers active at the same time as it may extend the scanning time with extra lookups.)




The screenshot shows the 'SURBL' configuration window. It has a title bar with standard icons. The window is divided into several sections, each with a green arrow icon and a title:

- Scan configuration**
  - Enable SURBL test: ☒
- Scan result actions**
  - Block the message: ☒
  - Quarantine the message: ☐
  - Notify the sender: ☐
  - Notify the recipient(s): ☐
  - Notify the administrator: ☐
- SURBL server list**
  - SURBL server list:

## RBL

The RBL event functions the same as the SURBL event does. Incoming messages are checked to see if any sending server(s) are included on the list of the RBL servers listed. If a match is found, the service specified will be performed, (block, notify, quarantine).

The RBL event may be limited to certain lines in the message. The default is to scan the entire header of a message. (It is not recommended to have more than two RBL list servers active at the same time as it may extend the scanning time with extra lookups.)




The screenshot shows the 'RBL' configuration window. It has a title bar with a save icon, a green arrow, a checkmark, and a refresh icon. The window is divided into three sections: 'Scan configuration', 'Scan result actions', and 'RBL server list'. In the 'Scan configuration' section, 'Enable RBL test', 'Enable connection drop', and 'Enable message header scan' are checked. 'Limit received header lines scanned' is unchecked. 'First received header line to scan' is set to 1, and 'Last received header line to scan' is set to 16. In the 'Scan result actions' section, 'Block the message' is checked, while 'Quarantine the message', 'Notify the sender', 'Notify the recipient(s)', and 'Notify the administrator' are unchecked. In the 'RBL server list' section, the 'RBL server list' field contains 'sbl-xbl.spamhaus.org' and 'bl.spamcop.net'.

RBL	
▼ Scan configuration	
Enable RBL test	<input checked="" type="checkbox"/>
Enable connection drop	<input checked="" type="checkbox"/>
Enable message header scan	<input checked="" type="checkbox"/>
Limit received header lines scanned	<input type="checkbox"/>
First received header line to scan	1
Last received header line to scan	16
▼ Scan result actions	
Block the message	<input checked="" type="checkbox"/>
Quarantine the message	<input type="checkbox"/>
Notify the sender	<input type="checkbox"/>
Notify the recipient(s)	<input type="checkbox"/>
Notify the administrator	<input type="checkbox"/>
▼ RBL server list	
RBL server list	sbl-xbl.spamhaus.org bl.spamcop.net

## IP Reputation

IP Reputation works much like the RBL interface does, in that it uses a black list, but also has a white list for common mail sources. But when used on a SMTP interface and configured for a connection drop, IP Reputation will temporarily fail messages from sources not found on either list. The temporary fail will allow the sending SMTP gateway to retry, and IP Reputation will allow a repeated unknown attempt to pass on to the Antispam filter. As with RBL, the header lines scanned may be limited and specified. (This can be used to skip lines added to the header by a proxy server or other service.)




The screenshot shows the 'IP reputation' configuration window. It has a title bar with a save icon, a green arrow, a checkmark, and a refresh icon. The window is divided into two sections: 'Scan configuration' and 'Scan result actions'. In the 'Scan configuration' section, 'Enable IP reputation test', 'Enable connection drop', and 'Enable message header scan' are checked. 'Limit received header lines scanned' is unchecked. 'First received header line to scan' is set to 1, and 'Last received header line to scan' is set to 16. In the 'Scan result actions' section, 'Block the message' is checked, while 'Quarantine the message', 'Notify the sender', 'Notify the recipient(s)', and 'Notify the administrator' are unchecked.

IP reputation	
▼ Scan configuration	
Enable IP reputation test	<input checked="" type="checkbox"/>
Enable connection drop	<input checked="" type="checkbox"/>
Enable message header scan	<input checked="" type="checkbox"/>
Limit received header lines scanned	<input type="checkbox"/>
First received header line to scan	1
Last received header line to scan	16
▼ Scan result actions	
Block the message	<input checked="" type="checkbox"/>
Quarantine the message	<input type="checkbox"/>
Notify the sender	<input type="checkbox"/>
Notify the recipient(s)	<input type="checkbox"/>
Notify the administrator	<input type="checkbox"/>

## SPF

Sender Policy Framework can be used with the GWIA and SMTP interfaces. Sender Policy Framework, (SPF) attempts to verify the sender of each email message, which can eliminate spoofed email and most backscatter attacks. For SPF to work correctly, the sending domain must have an updated SPF record set up in DNS. If the sending domain does not have a SPF record set in their DNS, then their mail will not be blocked. Setting up a correct SPF record will block messages from spammers who are pretending to be you, to your system.

To use SPF on a GWIA interface, you must correctly specify which line in the header of mail messages is to be used. If the mail system is using a relay or proxy which adds a line to the message, then you should set SPF to use the second line (2), otherwise, the line used should be set to one (1), which is the default.




The screenshot shows the 'Sender Policy Framework (SPF)' configuration window. It has a title bar with standard window controls. The window is divided into two main sections: 'Scan configuration' and 'Scan result actions'. In the 'Scan configuration' section, there are four items: 'Enable SPF test' (checked), 'Enable connection drop' (checked), 'Enable message header scan' (checked), and 'Header line number containing source IP address' (set to 1). The 'Scan result actions' section has four items: 'Block the message' (checked), 'Quarantine the message' (unchecked), 'Notify the recipient(s)' (unchecked), and 'Notify the administrator' (unchecked).

Sender Policy Framework (SPF)	
▼ Scan configuration	
Enable SPF test	<input checked="" type="checkbox"/>
Enable connection drop	<input checked="" type="checkbox"/>
Enable message header scan	<input checked="" type="checkbox"/>
Header line number containing source IP address	1
▼ Scan result actions	
Block the message	<input checked="" type="checkbox"/>
Quarantine the message	<input type="checkbox"/>
Notify the recipient(s)	<input type="checkbox"/>
Notify the administrator	<input type="checkbox"/>

SPF can be configured to perform connection blocks in conjunction with the SMTP interface, which drops the receiving connection of a message before the message transfer is complete, if the sending server fails to be verified by SPF. This saves bandwidth as well as denying the messages from spammers.

## Denial of Service

The Denial of Service option, only applicable for SMTP scanners, allows administrators to automatically deny connections to any address which attempts massive amounts of connections over a period of time. GWAVA automatically keeps a constantly updating list of addresses and their connections. Simple configuration and settings allow custom variables for this option.



The screenshot shows the 'Denial of service' configuration window. It has a title bar with standard window controls. The window is divided into two main sections: 'Scan configuration' and 'Denial of service settings'. In the 'Scan configuration' section, there are three items: 'Enable DoS detection' (checked), 'Enable connection drop' (checked with a lock icon), and 'Connection limit' (set to 90). In the 'Denial of service settings' section, there are two items: 'Watch period (seconds)' (set to 60) and 'Rejection time (minutes)' (set to 60).

Denial of service	
▼ Scan configuration	
Enable DoS detection	<input checked="" type="checkbox"/>
Enable connection drop	<input checked="" type="checkbox"/>
Connection limit	90
Watch period (seconds)	60
Rejection time (minutes)	60

For Denial of Service to function, it must be enabled along with the connection drop option.

### Enable Connection Drop

The connection drop option empowers GWAVA to automatically drop any incoming connection from a banned address. If the Connection Drop option is not enabled, GWAVA will track addresses, but no action will be taken on addresses which qualify for the Denial of Service protection.

### Connection Limit

This is the number of connections from any one address which the system will allow. This limit can be set to anything, but if enabled, this limit will be applied to every address sending mail to the SMTP server. The setting is defined as total allowed connections for the watch period.

### Watch Period


The Watch Period is the time to which the connection period applies. This is the setting which decides how long an address is maintained on the watch list. If the number of connections allowed is exceeded in the time specified here, the address will be added to the rejection list, and all incoming connections from that address will be automatically dropped. The setting is defined in seconds.

### Rejection Time

The Rejection Time is the amount of time a blacklisted address remains on the rejection list. Any address which is added to the rejection list will be automatically denied any connections to the GWAVA system. Addresses on this list will remain on this list for the specified time, and then be automatically removed from the list and connections will then be allowed again. An address released from this list will still be subject to the same connection limit and watch period which resulted in that address being added to the rejection limit in the first place. This essentially throttles the offending address to the connection limit over the amount of time listed in the rejection time setting; it does not permanently remove all message connections from the offending address. This setting is defined in minutes.

### Conversation Tracking


Conversation tracking keeps tabs of continued email correspondence between local users and their outside contacts. These email 'conversations' are, by default, automatically added to a white list as well as copied and added to the advanced learning engine as examples of good mail.



## Spam Reporting

The signature spam engine included with GWAVA is extremely accurate, however, it is not perfect and GWAVA still has a way to improve the engine. Spam Reporting is a method by which messages which are flagged as spam can be submitted and reported to the master system.

When turned-on, GWAVA will keep a clean, unaltered copy of all messages that make it through the system for three days. If a message that was scored as 'clean' by the signature engine is discovered to be spam, it can be searched for and the unaltered copy will be submitted and reported to the GWAVA systems as well as modify the local GWAVA rule set.



The screenshot shows the 'Spam Reporting' configuration window. It has a title bar with standard OS icons. The main area contains several settings:

- ☐ Enable spam report queue
- ☐ Generate spam report link on inbound messages
- Maximum queued message size (kb):
- ☐ Custom self-release footer signature
- Text:
- HTML:

Below these fields is a 'Notes' section:


Notes: Both signature templates must be filled in.  
HTML codes must be used for special characters, i.e. < should be written as &lt;;  
Place the text \$(release\_url) at the location for the release address.  
See the help for this page for more in depth details.


---

**Search message queue for spam to report**

From address:

To address:

Start date/time:  

End date/time:  

Max results to return:

Sorting:

Include reported messages: ☐

To facilitate quick reporting of spam, an automatically generated spam reporting link may be added to the messages which can simply be selected to report the offending message to the GWAVA system. The generated link may be customized in the provided fields, ensure to use proper syntax and fill out BOTH fields for a custom link.


## Text filtering

### Subject + Body

Subject + Body Text filtering searches the subject line and body of the message for a match to any filter specified. Filters must be added manually. GWAVA recognizes all plain text filters as well as standard regular expressions, or RegEx. GWAVA does not recognize RegEx ranges, (values in between { } braces), unless the entire RegEx string is followed by a '/' at the end.

### Subject or Body

Both the Subject and Body filters work identically to the Subject+Body filter except that the filters added to these sections are restricted to only the subject of the message for the subject filters, and likewise only the body of a message for the Body filters.




There are six optional actions or services for every interface event or filter that fires on a message:

**Block, Quarantine, Notify Sender, Notify Recipient(s), Notify Administrator, and Notify Defined Addresses.**

The action icons instead of the checkbox work as a global toggle. Selecting the icon globally toggles, activates or deactivates the event for every listed option.

The block and the quarantine options are not the same. If you select to quarantine a message, but do not select the block action, then the message will have a copy placed in the quarantine, but still be allowed to reach the destination mailbox. Blocking a message without selecting quarantine will simply prevent a message from entering the GroupWise system.




The different notification options are exactly as they are named and are active for every time the event fires. The Notify Defined Addresses sends a notification to the addresses defined in the custom address list. To add addresses, simply enter them into the provided window, separate multiple addresses with a comma, and save the changes. The custom addresses are only active for the text filter which the addresses are tied to.

In addition to the 'addresses' option, the 'Notes' option allows for any particular notes to be applied to the text filter. Notes does not modify the function of the filter, but is provided for convenience. To

modify the notes field, simply enter text into the provided field. Make sure to save the changes before leaving the page to commit the notes to the system.

## URL Filtering

URL Filtering is utilized by the Web Interface to block specified URLs from being accessed through the web filter. Any URL which has been specified will be blocked when placed in the URL filter and configured with a block action.




To enter a URL into the list, select the 'new filter' button and specify the URL. The syntax for specifying the URL accepts wildcards, but must match specifically, or the URL will not be detected. For instance, in order to block gwava.com, the URL could be entered in two different ways:

- `http://www.gwava.com*`
- `*gwava.com*`

The use of the asterisk is to guarantee that the URL is completely blocked. Though other forms may be utilized to block specific sections or services from sites, these are the recommended forms.

## Authentication Filtering

Authentication filtering is the process whereby GWAVA requires the user to authenticate to the proxy to be able to access the internet. Once enabled, all users are required to authenticate to gain access. To deny access or set specific actions to a specific user, add the user to the filter list.




To enter a user in the authentication filter, select the 'New filter' button and enter the user's name. Select the different actions desired for the specified user and save changes.

## Body Filter

The body filter used for the Web Interface works the same as the body filter for message scanning, except that the Web Interface scans requested web pages for key words. The end effect is the same in that offending pages are blocked.





To add a keyword or phrase to the body filter, click 'add filter' and enter the text desired. The body filter is not case sensitive. Save changes.

## MIME filtering


Every internet message passing through the mail system comes through as a MIME file. MIME filtering scans the message in its basic raw form, the MIME file, for patterns matching any filter specified by the Administrator. GWAVA does not come with any raw message filters pre-configured. The MIME filters work in the same way as the text filters do for events and options. To create an effective MIME filter, the original MIME file for an offending message must be examined to identify a string or variable to create the filter for. Any line or variable in a MIME file may be subject to a filter. Specify the filters in plain text. For instance, to create a filter to block out a specific character set; create a filter looking for 'charset=<desired character set>'.

I.e.

'charset=US-ASCII'


## Raw

The Raw message filter searches the message section of the message MIME file. Create filters in this section to target variables in the message section of a MIME file.




## Message Header

The Message header filter searches the header of the MIME file. Create filters in this section to target variables in the header of the MIME file.



## Oversize

The Oversize message event interface targets the total size of a message to make it subject to a block, quarantine, or notification. The maximum message size allowable is specified in kilobytes, enabled with a default of 8.1 MB. If you wish to allow larger messages through the system, increase the allowable size or disable the Oversize event.




The screenshot shows a window titled "Oversize message" with a standard toolbar. It contains two main sections: "Scan configuration" and "Scan result actions".

▼ Scan configuration	
Enable oversize message test	<input type="checkbox"/>
Maximum allowable message size (kB)	<input type="text"/>

▼ Scan result actions	
Block the message	<input type="checkbox"/>
Quarantine the message	<input type="checkbox"/>
Notify the sender	<input type="checkbox"/>
Notify the recipient(s)	<input type="checkbox"/>
Notify the administrator	<input type="checkbox"/>
Notify defined address(es)	<input type="checkbox"/>

## Undersize

The Undersize message event is designed to filter incomplete message files or 'blank message spam'. It may also be used to filter all messages below the standard message size in the system. The default size is 100 bytes, and may be tailored to each specific system. This interface is not enabled by default, and must be enabled before it becomes active.




The screenshot shows a window titled "Undersize message" with a standard toolbar. It contains two main sections: "Scan configuration" and "Scan result actions".

▼ Scan configuration	
Enable undersize message test	<input type="checkbox"/>
Minimum allowable message size (bytes)	<input type="text" value="100"/>

▼ Scan result actions	
Block the message	<input type="checkbox"/>
Quarantine the message	<input type="checkbox"/>
Notify the sender	<input type="checkbox"/>
Notify the recipient(s)	<input type="checkbox"/>
Notify the administrator	<input type="checkbox"/>
Notify defined address(es)	<input type="checkbox"/>


## Fingerprinting

The Fingerprinting event interface works like a virus interface does, to identify the patterns of files for specific file types. This allows the fingerprinting interface to identify renamed .exe or other file types, and keep them from advancing through the system. See the Fingerprinting interface for defaults and all included file types. Additional file types cannot be added manually. Default actions for active file types are block and quarantine.



## Image Analyzer

The image analyzer scans images in messages for illicit material. The image analyzer can be configured to check images of all different sizes. Default settings are shown. It is not enabled by default. Image Analyzer services are an additional service requiring an additional license to be purchased. Please contact GWAVA sales to acquire the Image Analyzer license.



The screenshot shows a window titled "Image analyzer" with a standard Windows-style title bar. The window is divided into two main sections: "Scan configuration" and "Scan result actions".

**Scan configuration**

Enable image analysis	<input type="checkbox"/>
Minimum image width (pixels)	0
Minimum image height (pixels)	0
Sensitivity (0-100)	65
Threshold (0-100)	75

**Scan result actions**


Block the message	<input type="checkbox"/>
Quarantine the message	<input type="checkbox"/>
Quarantine for administrator	<input type="checkbox"/>
Notify the sender	<input type="checkbox"/>
Notify the recipient(s)	<input type="checkbox"/>
Notify the administrator	<input type="checkbox"/>
Notify defined address(es)	<input type="checkbox"/>

By default, the Image Analyzer is configured to flag any image of any size that matches a score level defined by sensitivity and then violates a threshold. The Image Analyzer scores images based on different criteria including skin tone colors, shapes, etc. all combined to generate the score. The sensitivity determines the detected criteria and therefore the score, while the threshold dictates at what score the message triggers action.

As with the other filters, the image analyzer can be set to block, quarantine, or notify, or all the above.

## Attachment types

The Attachment types event interface reads the extension of an attachment and either allows or blocks the file depending on the extension. Because this is not dependent on the file's profile, as the fingerprinting interface does, additional file extensions may be specified as desired. See the Attachment types event page for default attachment types. For all default types active in the system, the default action is to block and quarantine.




### Source address filter (from:)

The Source Address event allows specific addresses to be specified for a block, quarantine, or different notifications. The Source Address filter searches incoming message's 'From:' address for a match with any specified addresses in the list. There are no default addresses in this list.

Wildcards are recognized, though not recommended unless an entire domain is desired to be blocked. For example, to block a single address, add the undesired "username@domain.com" as a filter and specify the desired action: block, quarantine, notify.


To block an entire domain, enter the undesired "\*@domain.com" as a filter and specify the desired action. A filter that specifies an entire domain, will act on all messages from that domain.



### Destination address filter (to:)

The Destination address filter works the same way as the Source address filter, except for the 'To:' address instead of the from address. This can be used to deny specific users messages. Specify the address with standard syntax: "username@domain.com". This is useful for when an account is no longer desired to be used, or when a notification is desired for each time a message comes to a specific user.


When notifications are set for a specific user, note that each time a message is sent to a specified address then the filter will fire and a notification will be sent, even if the message was blocked as spam. Every message is scanned by every enabled interface, (except for the SPF and IP reputation scans if they are configured for connection drop).



## IP Address Filter

The IP Address event searches the message for a match to any specified address in the filter list. There are no default addresses listed. If any IP address contained in the MIME file matches one specified here, the selected event will be processed. Specify filters with the bare IP address desired.

I.e. 192.168.56.21




The screenshot shows a window titled "IP address filter". It has a "Scan configuration" section with a checkbox for "Enable ip address filter" which is checked. Below this is a "Filter list" section. At the bottom of the window, there are buttons for "New filter" and "Multi-line import", and a table with columns "Actions", "Notes", and "Notify".

## Message services

GWAVA can perform three general services for the entire message system. These services are performed on all messages passing through the system.

### *Global quarantine*


The Global quarantine message service acts exactly as it sounds; every single message passing through the mail system has a copy placed into the quarantine. This option overrides all other settings in the system, including forced deletion of virus infected messages; a copy will be placed in the quarantine.



The screenshot shows a window titled "Global quarantine". It has a "Settings" section with two checkboxes: "Quarantine all messages (admin only)" and "Quarantine all messages". Both checkboxes are currently unchecked.

## Signatures

The Signatures service instructs GWAVA to add any specified signature to the selected directional mail. Signatures WILL NOT WORK with POA interfaces. If incoming mail is selected, all messages coming into the mail system will have the signature appended to the end of the message. The same applies to outgoing mail messages. If selected, all outgoing mail will have the specified signature added to the end of the message.



The screenshot shows a window titled "Signatures" with a standard Windows-style title bar. Inside the window, there are two checkboxes at the top: "Enable signature service for outgoing mail" and "Enable signature service for incoming mail". Below these is a section titled "HTML Signature Editor" which contains a large text area for editing the signature and a vertical toolbar on the right with buttons for "Bold", "Italic", "Underline", "New Line", "New Para.", and "Horiz. Line". Underneath the HTML editor is a section titled "HTML Signature Preview" with a large rectangular area for viewing the signature. At the bottom is a section titled "Text Signature Editor" with a large text area for editing a plain text signature.



### ***Blind Carbon Copy***

The Blind Carbon Copy event instructs GWAVA to create a BCC message and send it to the specified address. (If you wish to send to multiple addresses, an email group should be created in the email system.) This may be specified by a custom or default event, simply by selecting the event from the list provided. For instance; if an administrator desires to be sent a BCC each time a specific user or address receives a message, they may specify a destination address event, and then select that interface address under this list and specify the BCC address. After saving changes, the BCC will become active in a few moments.

**Blind Carbon Copy**

☒ Send BCC to Administrator

☐ Send BCC to

**Events that are flagged for Blind Carbon Copy**

- ☐ Antivirus
- ☐ Oversized message
- ☐ Undersized message
- ☐ Antispam heuristics
- ☐ SURBL
- ☐ RBL
- ☐ IP reputation
- ☐ SPF
- ☐ Image analysis
- ☐ Fingerprinting
- ☐ Message subject+body filter
- ☐ Message body filter
- ☐ Message subject filter
- ☐ Raw message filter
- ☐ Message header filter
- ☐ Attachment name
- ☐ Source address
- ☐ Destination address
- ☐ IP address


## Exceptions

GWAVA is designed to avoid needing exceptions. When using the Signature spam engine, there should be no reason to create exceptions on a regular basis, as caught mail will be due to a setting in one of the other filters. If mail is caught incorrectly by the oversized message, fingerprint, subject or body filters, etc... the offending engine should be adjusted. Adjust the interface settings if exceptions are created regularly; the exception list should be used sparingly, when no other option applies.

GWAVA provides the option to create exceptions to the event interfaces, to allow specific messages or addresses to pass filters that would otherwise have blocked them. An exception in GWAVA consists of two main parts: the identifying item and the event interface(s) it is exempted from. Until you have specified both, the exception will not be valid and cannot be saved.

The different exception pages are essentially the same, though their function and syntax vary. Make sure you use the appropriate exception for each situation.

The exception menu items which have folders are expandable to allow the selection of specific filters inside each event interface. For example, this allows the creation of an exception from specific file types from the fingerprinting system, instead of the entire event filter, though the entire filter may also be selected.



If an expandable event interface does not have any filters, it will show a “No items found” notification. Since each exception adds time, though negligible, to the scanning process, only add necessary exceptions to the system.


### Source address (From:)

The Source (From:) Exceptions are based on the ‘From:’ address listed for the message. The majority of exceptions are created here, as it is the easiest exception to correctly create. Source exceptions are used to allow an outside address to pass by a specific filter or filters. These exceptions are specified in the following syntax:

user@domain.com

The address exception should exactly match the source address listed on the message. Source Exceptions also recognize wildcards, and, though it is not recommended, entire domains may also be specified. (i.e. \*@domain.com ) However, if a simple wildcard is specified, such as \*msn.com, then any message with ‘msn.com’ included in the address will be matched with the exception and will pass the selected interfaces.

After adding the exception, make sure you select an interface to apply the exception to, then save the change by clicking the colored disk to make the exception active.



### Destination address (to:)

The Destination address (to:) exception list uses the “to:” address listed on the message to identify messages exempted from specific filters. Destination exceptions are used to allow a specific internal user to receive messages normally blocked by a specific filter or filters. For a destination exception to work, the domain the excepted address belongs to must be managed by GWAVA. DO NOT use wildcards with destination exceptions. Creating a destination exception allows all external mail coming to the specified address to pass the selected filter. If a wildcard and domain is specified here, all external mail to that domain will be exempted from the selected filter and spam will be allowed through. Use the same syntax as the Source Address exceptions. (i.e. user@domain.com)

### Message subject

The Message subject exception uses the subject line of the message file to identify and apply an exception. The Message Subject exception should not be used often, as repeated conversations are better identified by [‘Conversation Tracking’](#) (found under the Non-spam auto-learn section). The syntax is specified in plain text.

### Message text

Message text exceptions search the text of a MIME file for matches to any specified exception. Regex and plain text are accepted. Specific and exclusive signatures are a good target for message text exceptions.

### Message header

Message header exceptions search the MIME header for a match to a listed exception. Header exceptions should be specified with regex or plain text as found in the header of the message.

## Message source

This exception searches the entire MIME file for specified text to identify a trusted server or mail source. This is used only when the identifying information is not in a specified place in the MIME file. Any message sent from the specified source will be allowed through to the system.


## IP Address

The IP Address exception searches for a specified IP address anywhere in the message header. IP addresses specified in this exception list are considered 'trusted', and no messages from these IP addresses will be blocked.

## Authenticated User

The Authenticated User exception list offers a chance for administrators to exempt specific users from Web Interface scanning criteria. This exception only applies to Web Interface scanners, as all other applications utilize the full email address. This option will exempt an authenticated user from restrictions placed on the Web interface due to the URL filter.

To add a user to the exception list, enter the user name into the 'Add' window and select the 'add' button. Once the user has been added, the URL exception must be checked and then saved.



## GWAVA Quarantine system

The GWAVA Quarantine system has two different control levels for the interface: the general user interface, and the Administrator interface. When login credentials are passed to the Quarantine system, QMS, (Quarantine Management System), contacts the GWAVA management system for administrator accounts, and the GWIA for normal users. QMS uses a simple SMTP authentication to check for a valid user and password against the GWIA, so the same password used by system users is used to login to manage their personal quarantine. Admin users, setup in the GWAVA management console, should only use their username and password to login. Normal system users should use their full email address and GroupWise password to authenticate.

i.e.

admin

password

-or-

[user@domain.com](mailto:user@domain.com)

password

## User interface

The User interface is different from the Admin interface in that the options available to normal users is extremely limited. Only the Quarantine and Options tabs are available, and they only contain data related to the logged-in user.

Only the mail sent to the operating user is shown, (unless specified by the administrator, only the mail sent to a user's email address will be shown; Administrators may specify more than one address to be managed by a single user). Users may be granted rights, or have them removed from the administrator. By default,


The user's options tab offers specific login, timeout, whitelist, blacklist, and display settings for their specific account. Users do have the ability to whitelist and blacklist addresses; however, this ability only applies to their specific address, and does not affect the rest of the system. Any user's individual whitelist and blacklist is accessible through the administrator interface, and can be modified and managed by the administrator. The individual lists are located at **Options | Whitelist \ Blacklist | <select specific user>**.

## Administrator interface

The administrator user created during the initial GWAVA user creation is the default account with administrator rights to the Quarantine system. When the administrator account logs into QMS, the following window is displayed listing all, if any, spam added to the quarantine system in the last three days, by default.

### Quarantine

The quarantine tab lists messages and message information. It is important to pay attention to the last two columns: Event and Score. The score is a threshold level for the anti-spam engine, and the event is the interface event, or events, which caused the message to be added to the quarantine. This information is critical to creating effective exceptions and fine tuning the scanning engine. The quarantine tab allows for the selection, white or blacklisting, forwarding, release, and searching of messages in the database.



The screenshot shows the GWAVA Quarantine interface. On the left is a search sidebar with options like 'Search for', 'Subject', 'Contains', 'Message Age', and 'Show Advanced'. The main area displays a table of quarantined messages. The table has columns for Date, Subject, From, Recipient, Event, and Score. The messages listed are all from 'james@gwava.com' to 'chris@gwava.com' and are categorized as 'Text filter' with a score of 0.0. The interface also includes a top navigation bar with tabs like 'Quarantine', 'Options', 'Digest', 'Users', 'Groups', 'Globals', and 'Tools'.

Date	Subject	From	Recipient	Event	Score
14-Jan-2012 00:18:21	A message from the Dean of the Ivey Busine	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:21	A message from the Dean of the Ivey Busine	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:20	RE: demosrv in Fortune!	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:20	RE: Outstanding Stock Options and Restrict	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:20	(none)	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:20	Buy a universal remote / home safe	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:20	RE: the colonel	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:19	(none)	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:19	ibuycrap.orgpaq Deal:	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:19	Re: Plans...	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:19	Re: Plans...	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:19	New Deals from Friday April 7	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:19	Howdy!	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:19	(none)	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:19	RE: Outstanding Stock Options and Restrict	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:18	Pick me up!	james@gwava.com	chris@gwava.com	Text filter	0.0
14-Jan-2012 00:18:18	RE: Estimate of move costs	james@gwava.com	chris@gwava.com	Text filter	0.0

The search function of the quarantine tab provides multiple methods of specifying criteria to search the database. As with any search engine, the more information known about the target object, the more precise the results will be. There are two main ways to search; using key words or terms and browsing by categorical results.

Searching by key words or terms is the faster, more precise way to locate a message, but make sure that any key terms provided are spelled correctly to avoid accidentally excluding the target object from the search engine. To begin a search on specified criteria, select the **Search** button.

Searching by browsing through categorical results may seem tedious, but there are several categories which may be included or excluded to considerably tighten the search results. As with the key words and terms, ensure that any items excluded from the search results does not contain the target message as well. A combination of both methods may produce the best results on a consistent basis.

Search preferences and settings are specified on the Left side of the quarantine tab window. Expanding the **Advanced** criteria section allows the limiting to events, or exclude events from the search results. For instance, most messages in the quarantine will be caught by multiple event interfaces, which may cause the result list to bloat. Limiting the results to the oversize message event may help find the desired message, but if the RBL and SURBL event filters are excluded, the result list is significantly reduced, as any message caught by the oversize message filter and SURBL or RBL will not be shown.

**Message Status**, (released, forwarded, deleted), are 'include' options which act the same as the 'limit to' events listed above.

**Sort Results by** re-orders the results list by the selected option. Default sorting is by date.

The Message Age is also a very useful criterion, which limits the results to a time frame. The date of any quarantined message in QMS is given as the time stamp set in the message MIME file. To set a custom date range, select the custom date

range button and then specify the date range from the subsequent popup window. The window provides miniature

calendar selection tools to specify the date range.

If the **Message ID** is known, (i.e. from the message digest), the message ID may be used to immediately call up the desired message.

To specify a key word or term to locate the message, select the specific key word category at the top of the search pane. The search engine needs to know both where and what it is looking for. First specify where the search engine is to look in the database. The default search field is the 'sender', or the sender's user name/address. If the 'equals' is selected, ensure exact matching spelling to the desired criteria.

Using the + and – buttons, multiple search terms may be specified or removed from the active search.


Any search may be saved by selecting the "Stored Searches" icon at the top of the search pane. The **Stored Searches** function spawns a save or load window which prompts the user to either save, delete, or load any previously saved search sessions.

The toolbar across the top of the quarantine tab window provides functions to


quickly manage quarantined mail. The magnifying glass exposes and hides the search window, and the other main tools are labeled.



**Release** – Releasing a message from the quarantine tells GWAVA to return that message back to the mail stream, where it will be delivered to the original recipient, unchanged. Select a desired message(s) by placing a check in the associated checkbox, and then select the release button from the toolbar. Verify that you wish to release the message.



**Forward** – Forwarding a message from the quarantine does not automatically send the message to the original destination(s), but allows the admin to send mail to any recipient or recipients he desires. You may forward the message in the message body, or send as an attachment, as well as define the 'From:' field of the message.




## Ham

The 'Ham' button reports selected mail as incorrectly identified 'spam' caught in the system. This setting only applies to the Signature spam engine, and will not have an effect on any other filter.

## White List


When a message is selected for white listing, the system is actually creating a source exception in the Management database. As with all exceptions, white listing requires an address, and at least one event to bypass. Be sure to select the event which the message was quarantined for, plus all other desired events.



<input type="checkbox"/>	Date	Subject	From	Recipient	Event	Score
<input checked="" type="checkbox"/>	14-Apr-2009 20:26:06	Out of the Office	lotsdmail@gwava.com	ernie@buycrap.org	Spam threshold 5 ...	1.0
<input type="checkbox"/>	14-Apr-2009 20:25:57	Out of the office	jason@gwava.com	craig@buycrap.org ...	Spam threshold 5 ...	1.0

The quarantining event for each message is listed on the message row under the quarantine tab. The event column may hold more than one event per message, if there is more than one event listed, a drop-down menu will be available to display the different events for each message.


Both the white and black list options allow you to select different address options. These options correlate with different exception or black list types or entries. It is up to the Administrator which type of white list exception or black list entry to create.






## Black List

Black listing a message instructs the GWAVA system to always block messages from the Address selection (Source address, source domain, recipient address, recipient domain, or a combination of both the source and the recipient address or domain.) Blacklisted addresses' or domains' messages are added to the quarantine.



## Delete

The Quarantine Management system automatically deletes messages after the specified retention time. (Default is set to retain messages for 30 days – located under the **Globals | Pruning** tab.) Because the Quarantine is set to automatically manage message age and database size, there is no reason to delete messages from the quarantine. Messages deleted by users will only be completely removed from the system if all destination users have deleted their copy. However, messages deleted by the Administrator will be completely removed from the system.




## Options

Users and Administrators have access to the Options tab. User's only have access to options regarding their own address and quarantine settings. Administrators have access to everything by default, and as such, the only tabs in this menu which are useful for Administrators is the **Miscellaneous** tab, which holds account preferences, and the Whitelist and Blacklist tabs – which contain the whitelists and blacklists for individual users. These lists are not global lists, but only apply to the specific user who created it. To modify the user's list, select the user desired and view the list. Users will only show up in the system if they have received mail which has been added into QMS. Addresses may be added or removed from any specified user's list.

## Core settings

The Core settings tab under Options, displays the basic information which categorizes the currently active user. The currently active user, the UserID, Group, and managed address(s), and password. (The password will either be stored in the GWAVA Management console (GWAVAMAN) or authenticated through the GroupWise system.)



## Addresses

The screenshot shows the 'YOUR ADDRESSES' tab selected in the top navigation bar. The main heading is 'YOUR ADDRESSES' in green. Below it, a paragraph explains that these are e-mail addresses considered part of the user's identity for viewing messages, applying blacklists, whitelists, and deletes. It lists two actions: 'Remove all addresses except addresses that are inherited from a group.' and 'Add additional addresses, if you can authenticate to GroupWise with the address. (If you cannot, your QMS Admins may add them for you)'. A red note states: 'chris@buycrap.org will be validated and added after you click the SAVE CHANGES button'. Below this is a large empty text area for addresses, with a 'Remove Selected Address' button to its right. At the bottom, there are input fields for 'New Address' and 'Password', and an 'Add New Address' button.

Users have the option to add a managed address to their account, which will add the managed address' mail to the quarantine results of the user who added the additional address. To add a managed address, a user must provide the desired address, and the GroupWise password for that address. If a user cannot authenticate to the GroupWise system for an additional address, the address will not be added as a managed address. The Administrator may add any address to any other address in the system without needing to authenticate. Administrator added managed addresses are configured under the Users tab.

## Rights

The Rights tab lists the rights to actions which each user has. Administrators have all rights. Users may be granted specified rights to manage mail by the administrator, or by virtue of group in which they reside.

The screenshot shows the 'RIGHTS/GROUP' tab selected in the top navigation bar. The main heading is 'RIGHTS/GROUP' in green. Below it, a paragraph explains that rights define what can be done in the QMS, including explicitly assigned rights and inherited rights from Group Membership. Only QMS Admins can change these values. Below the text is a table with two columns: 'Rights' and 'Release/Delete'. The 'Rights' column contains a single entry 'Rights'.

## Event Scope

The Event Scope is an administrator level tab; users do not have this tab in their interface. Each user has rights to release mail by default. The Event Scope lists the release rights for the logged-in user. If a user has rights to release a filter type of mail, then any messages quarantined for that event will be available to be released to the receiving user.

The screenshot shows the 'EVENT SCOPE' tab selected in the top navigation bar. The main heading is 'EVENT SCOPE' in green. Below it, a paragraph states: 'As an Admin, you may whitelist, release, and/or display any message for any event.'

Admin may release any mail type in the system.

## Miscellaneous

Account settings for the logged-in user are kept under the miscellaneous tab. The settings under this section are all available to be modified, as they only apply to the user's account. Forwarded messages may have a comment added to them as a default action, as well general configuration for the quarantine display.

The screenshot shows the 'Miscellaneous' tab in the QMS settings interface. It contains three main sections: 'COMMENT', 'DATE / TIME FORMATS', and 'DISPLAY OPTIONS'. The 'COMMENT' section has a text area for setting a default comment. The 'DATE / TIME FORMATS' section has dropdowns for 'Date' (set to 'Day-ShortMonth-Year') and 'Time' (set to '24 Hour'). The 'DISPLAY OPTIONS' section has several checkboxes: 'Messages displayed per page' (25), 'Default time frame' (Last 3 days), 'Show icons only on toolbar' (unchecked), 'Hide search panel at startup' (unchecked), 'Wrap subjects' (unchecked), and 'Allow horizontal scroll' (unchecked). Below these is the 'SESSION TIMEOUT' section with a text input for 'Time (minutes)' set to 480.

Core Settings	Addresses	Rights	Event Scope	Miscellaneous
<b>COMMENT</b>				
The default comment appended to forwarded messages can be set here.				
<div>Comment</div>				
<b>DATE / TIME FORMATS</b>				
Defines how dates and times are displayed				
Date: Day-ShortMonth-Year				
Time: 24 Hour				
<b>DISPLAY OPTIONS</b>				
Messages displayed per page: 25				
Default time frame: Last 3 days				
Show icons only on toolbar: <input type="checkbox"/>				
Hide search panel at startup: <input type="checkbox"/>				
Wrap subjects: <input type="checkbox"/>				
Allow horizontal scroll: <input type="checkbox"/>				
<b>SESSION TIMEOUT</b>				
Time in minutes, to expire an inactive login session				
Time (minutes): 480				

## Digest

GWAVA can be setup to send regular reports to users when mail is blocked from a users address. Messages listed on the GWAVA digest can be released directly from QMS via a web link for each message. A working digest setup requires three things: an enabled user list, schedule, and an event list.

## Settings

The digest service must be enabled before digests are sent. Message removal settings when a message is released from the digest, are set here. If the message is not removed after release, it is possible to re-release messages, resulting in multiple copies of the same message sent from QMS to the recipient.

By default, the digest service sends digests to all users. If you wish to specify digested addresses, or to exclude addresses from the digest, you may specify them in the custom address list, then select the appropriate digest recipients option from the drop-down menu.

The screenshot shows the 'Settings' tab for the digest service. It includes checkboxes for 'Enable digest services', 'Remove message from users quarantine when released', and 'Remove message from QMS when all recipients have released their copy'. Below these are fields for 'Digest Template' (digest2\_master.xml), 'Maximum digest rows' (50), and 'Release button address'. A dropdown menu for 'Digest recipients' is set to 'Send digest to all users'. At the bottom, there is a 'Custom address list' section with a 'Remove selected' button (marked with a red X) and an 'Add new' button (marked with a green plus) next to an empty text input field.

Settings	Schedule	Events	Manual Release
<input checked="" type="checkbox"/> Enable digest services			
<input checked="" type="checkbox"/> Remove message from users quarantine when released			
<input checked="" type="checkbox"/> Remove message from QMS when all recipients have released their copy			
Digest Template: digest2_master.xml			
Maximum digest rows: 50			
Release button address: (blank for default)			
Digest recipients: Send digest to all users			
Custom address list			
Remove selected			
Add new			

## Schedule

The digest service will be processed and sent to users on the schedule set here. A check mark in the provided boxes notes an active hour time. Only the provided times are available. Clicking on the time or the day, (8:00am, Mon), constitutes a global selection for that time or day.

A recommended setting for different offices and users is impossible, though a reasonable setting for the system would be to send a digest in the morning, after lunch, and finally an hour before users leave, to allow time to catch any missed good mail on the day they are processed. The digest process is not cumulative, and only messages added to the quarantine which have not been previously listed on digest will be on the next digest. So, in the previous schedule, only messages received after the previous day's last digest up to the morning digest will be listed on the morning digest, and only messages from after the morning digest to the after lunch digest will be listed, etc...

Settings	Schedule	Events	Manual Release				
	Sun	Mon	Tue	Wed	Thu	Fri	Sat
Midnight	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
1:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
4:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
6:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
7:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
8:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
9:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
10:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
11:00am	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Midday	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
1:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
4:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
6:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
7:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
8:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
9:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
10:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
11:00pm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Settings	Schedule	Events	Manual Release
	Digested events	NEVER digested events	
Attachment filter	<input type="checkbox"/>	<input type="checkbox"/>	
Fingerprint	<input type="checkbox"/>	<input type="checkbox"/>	
Header filter	<input type="checkbox"/>	<input type="checkbox"/>	
IP address	<input type="checkbox"/>	<input type="checkbox"/>	
IP reputation	<input type="checkbox"/>	<input type="checkbox"/>	
MIME filter	<input type="checkbox"/>	<input type="checkbox"/>	
Oversized message	<input type="checkbox"/>	<input type="checkbox"/>	
RBL	<input type="checkbox"/>	<input type="checkbox"/>	
Recipient filter	<input type="checkbox"/>	<input type="checkbox"/>	
SURBL	<input type="checkbox"/>	<input type="checkbox"/>	
Sender filter	<input type="checkbox"/>	<input type="checkbox"/>	
Sender policy framework	<input type="checkbox"/>	<input type="checkbox"/>	
Spam threshold 1	<input type="checkbox"/>	<input type="checkbox"/>	
Spam threshold 2	<input type="checkbox"/>	<input type="checkbox"/>	
Spam threshold 3	<input type="checkbox"/>	<input type="checkbox"/>	
Spam threshold 4	<input type="checkbox"/>	<input type="checkbox"/>	
Spam threshold 5	<input type="checkbox"/>	<input type="checkbox"/>	
Text filter	<input type="checkbox"/>	<input type="checkbox"/>	
Undersized message	<input type="checkbox"/>	<input type="checkbox"/>	
Virus	<input type="checkbox"/>	<input type="checkbox"/>	

\* **Important note:** 'NEVER digested events' are used in situations where a message contains more than one event, for instance a spam message that ALSO contains a virus. In this situation, chances are that a digest should not be generated for the message because of the virus, even though it is also a spam message.

## Events

Like the schedule, the digest must be told which events to list on the digest. Messages caught for an event with a check under the 'Digested events' column will be listed on the digest. **Messages listed on the digest can be released from the digest, even if the user does not have QMS rights to release that event.** If an event is listed on the digest, it is assumed that the administrator wishes to allow the users to release the messages listed.

If a check is placed in the 'Never digested events' column, messages caught for that event will never be listed on the digest, even if it is also caught for a digested event. Selecting 'Virus' is an example of use for this section, (if viruses are quarantined), as a message

with a detected virus will never be listed on the digest and cannot be released from the quarantine unless the user has QMS rights to release that event.

## Manual Release

The digest may also be sent at any given time. The Digest works on a time stamp, which catalogs and lists mail in the quarantine if they are newer than the time stamp and fit the event list. Manual Release allows the admin to release a digest at any given time, by selecting the 'Send Digest' button. Sending a default manual release sets the digest time stamp.

The digest time stamp may also be manually set to affect the mail listed on the next released digest. This may be used to add additional mail to the manual digest. Select the time stamp desired and click 'Set'.

The screenshot shows a web interface with a top navigation bar containing 'Settings', 'Schedule', 'Events', and 'Manual Release'. The 'Manual Release' tab is active. Below the navigation bar, there are two main sections: 'Digest release period' and 'Custom digest release'.

**Digest release period**

The current digest time period is 7 days (default).

Changing the digest start date to an earlier time than the current period will cause the global digest to resend previously digested items to your users. Please be sure you understand the impact of this action before updating this setting. Global digests are released from the start time up to the time of the release, and the next digest start period will be reset to the current time.

Change digest period start: [20] [Apr] [2009] [10] [01] [Set]

**Custom digest release**

Release the digest for a defined time period to the selected range of users.

Start date: [20] [Apr] [2009] [10] [01]

End date: [21] [Apr] [2009] [10] [01]

Select users

☒ admin

☐ Release this address [ ]

☐ Release to all users (with global digest rules)

☒ Update global digest start period on release to all

[Send Digest]

A custom digest may be sent to specific users, or all users, with a specific time frame. This bypasses the usual user list, and does not set the time stamp, unless all users are selected as the release group.

## Users

The Users tab allows the configuration of different user accounts, their rights, managed addresses, and miscellaneous settings. Selected users have their settings loaded for each different tab, and are available for management. (Only users who have logged in or have been added by the administrator will be listed. If a desired user is not listed, you may add them by specifying the exact address of the user in the 'UserID' and 'Primary E-Mail Address' sections, then selecting 'Add User' and saving changes. The default setting for authentication is via SMTP. Group membership may be set as desired.)

### Core settings

The Core settings tab contains the basic settings for each user. The user ID, authentication, email address and group membership are all displayed. The authentication method is important to allow users to log into QMS. By default, the authentication for all users which are not administrators is to use SMTP authentication with the full address as the user name. If the GWIA is not available for SMTP user authentication, then the only authentication method which will work will be built-in GWAVA credentials.

The screenshot shows the 'Core Settings' tab for the 'admin' user. The 'UserID' is 'admin', the 'Authentication Method' is 'Built-in GWAVA credentials', the 'Primary E-Mail Address' is 'admin', and the 'Group Membership' is 'default'. A list of permissions for Admin rights is shown on the right, including seeing all messages, managing addresses, blacklisting/whitelisting, and deleting messages. A note at the bottom suggests creating a separate 'ordinary' user account for restricted capabilities.

Core Settings	User Rights	Event Scope	Addresses	Miscellaneous
<b>Core SETTINGS</b>				
UserID	admin			
Authentication Method	Built-in GWAVA credentials			
Primary E-Mail Address (used for SMTP authentication)	admin			
Group Membership	default			

### User Rights

User Rights allows the administrator to modify and set rights for specific users in the system. User Rights provides access to the basic actions of a user in QMS; delete, forward, and releasing messages. Full admin rights can be granted to any user specified.

The screenshot shows the 'User Rights' tab for the 'admin' user. The 'Full Administrative Rights' checkbox is checked. Below it, 'Delete Messages', 'Forward Messages', and 'Release Messages' are listed. A note at the bottom states that the following rights are additionally inherited from the user's group membership: 'Delete Messages' and 'Release Messages'.

Core Settings	User Rights	Event Scope	Addresses	Miscellaneous
<b>USER RIGHTS</b>				
Rights explicitly granted to the user.				
<input checked="" type="checkbox"/> Full Administrative Rights				
<input type="checkbox"/> Delete Messages				
<input type="checkbox"/> Forward Messages				
<input type="checkbox"/> Release Messages				
The following rights are additionally inherited from the user's group membership:				
Delete Messages				
Release Messages				

The selected user's rights are shown. If a user's right to delete or release messages is granted by the user's group membership, the user must be moved to a new group without those rights, or the original group rights must be modified to remove the undesired actions.

## Event scope

Each user can have specific rights to release messages which have been flagged for specific reasons. If, for example, a specific user may require the right to release messages flagged by the oversize message filter, while that may not be allowed for the rest of the users in the system. If a message has been flagged for multiple events, the user must have rights to release all events flagged on the message or the message will not be released.

The screenshot shows the 'Event Scope' tab for the 'admin' user. The interface includes a top navigation bar with tabs: Core Settings, User Rights, Event Scope (selected), Addresses, and Miscellaneous. A message at the top left states 'User admin loaded.' Below this is a list of users with 'admin' selected. To the right of the list are buttons for 'Add User', 'Edit User', and 'Remove User'. Further right, a section titled 'The selected user has Admin rights. This means:' lists several permissions:
 

- The user can see all messages in the database. An 'ordinary' user can only see messages that have a Container and that are linked to their Primary Address or their secondary addresses.
- The Managed Address list has no function.
- The user may blacklist and whitelist messages.
- Whitelisting a message can be done selectively for any and ALL events.
- Deleting a message removes it for ALL users.
- Any Group rights are unnecessary, and any rights other than Admin rights are superfluous.

 Below this list is a note: 'If you want to restrict these capabilities, you may wish to create a separate 'ordinary' user account for your usage and switch between the two as needed.'

The main section is titled 'EVENT SCOPE' and explains: 'This defines what events a release for an ordinary user applies to.' It contains a grid of checkboxes for various filters:
 

<input type="checkbox"/> Attachment filter	<input type="checkbox"/> Fingerprint	<input type="checkbox"/> Header filter
<input type="checkbox"/> IP address	<input type="checkbox"/> IP reputation	<input type="checkbox"/> MIME filter
<input type="checkbox"/> Oversized message	<input type="checkbox"/> RBL	<input type="checkbox"/> Recipient filter
<input type="checkbox"/> SURBL	<input type="checkbox"/> Sender filter	<input type="checkbox"/> Sender policy framework
<input type="checkbox"/> Spam threshold 1	<input type="checkbox"/> Spam threshold 2	<input type="checkbox"/> Spam threshold 3
<input type="checkbox"/> Spam threshold 4	<input type="checkbox"/> Spam threshold 5	<input type="checkbox"/> Text filter
<input type="checkbox"/> Undersized message	<input type="checkbox"/> Virus	

Below the grid, it states: 'The following event scopes are additionally inherited from the user's group membership:' followed by a list:
 

- RBL
- SURBL
- Spam threshold 4
- Spam threshold 5

Rights granted by group membership are listed at the bottom of the page. See the Groups tab to modify a user's membership to a group, or group rights.

## Addresses

Any email address may be associated with any other user account in the system. This allows any user to modify and manage any quarantined mail for any address entered into the system, as that user would manage their mail.

The screenshot shows the 'Addresses' tab for the 'admin' user. The interface is similar to the previous one, with the 'Addresses' tab selected in the top navigation bar. The 'User admin loaded.' message and the user list with 'admin' selected are present. The 'Add User', 'Edit User', and 'Remove User' buttons are also visible. The 'Admin rights' section and its list of permissions are identical to the previous screenshot.

The main section is titled 'MANAGED ADDRESSES' and explains: 'These are additional addresses beyond the primary e-mail address that constitute the user's 'identity'. A non-admin user will only view messages addressed to these e-mail addresses, and can only whitelist, blacklist, release, etc for these addresses. Users can self-add these, but only addresses which can authenticate against the GWIA. As an admin, you can add anything.'

Below this text is a large empty text area for adding addresses. To the right of this area are two buttons: 'Remove Selected Address' and 'Add'. Below the 'Add' button is a text input field labeled 'Address'.

This is especially useful for GroupWise systems which accept several different variants of a user name or different domains for the same user, allowing that user to manage all mail for their account in one location. As administrator, to add a managed address to a user, simply select the desired user from the user window, then specify the managed address(s) for that user in the managed address window, click 'add', then save changes. To remove a user's managed address, select the desired managed address from the address window, and click 'Remove Selected Address' then save changes.

## Miscellaneous

Miscellaneous contains the miscellaneous options for the selected user. These options are the same as those listed under the **Options | Miscellaneous** tab, and are self-explanatory. Any changes made should be saved before browsing to a different window or tab.

The screenshot shows the 'Miscellaneous' tab selected in a user management application. The interface includes a top navigation bar with tabs: Core Settings, User Rights, Event Scope, Addresses, and Miscellaneous. A red message 'User admin loaded.' is displayed. On the left, a list of users shows 'admin' selected. To the right of the list are buttons for 'Add User', 'Edit User', and 'Remove User'. A text box explains the implications of Admin rights for the selected user, listing capabilities such as seeing all messages, managing addresses, and deleting messages. Below this, several configuration sections are visible: 'COMMENT' (with a text input field), 'DATE / TIME FORMATS' (with dropdowns for Date and Time), 'DISPLAY NUMBER' (with a dropdown for Number of Items), 'MESSAGE AGE DISPLAY' (with a dropdown for Display), and 'SESSION TIMEOUT' (with a text input for Time in minutes).

Core Settings User Rights Event Scope Addresses Miscellaneous

User admin loaded.

admin

Add User Edit User Remove User

The selected user has Admin rights. This means:

- The user can see all messages in the database. An 'ordinary' user can only see messages that have a Container and that are linked to their Primary Address or their secondary addresses.
- The Managed Address list has no function.
- The user may blacklist and whitelist messages.
- Whitelisting a message can be done selectively for any and ALL events.
- Deleting a message removes it for ALL users.
- Any Group rights are unnecessary, and any rights other than Admin rights are superfluous.

If you want to restrict these capabilities, you may wish to create a separate 'ordinary' user account for your usage and switch between the two as needed.

**COMMENT**

The default comment appended to forwarded messages can be set here.

Comment

**DATE / TIME FORMATS**

Defines how dates and times are displayed

Date Day-ShortMonth-Year Time 24 Hour

**DISPLAY NUMBER**

How many items to display per page

Number of Items 25

**MESSAGE AGE DISPLAY**

How many days of messages should be displayed by default?

Display Last 3 days

**SESSION TIMEOUT**

Time in minutes, to expire an inactive login session

Time (minutes) 10



## Group Rights

The 'Group Rights' tab is essentially identical to the 'User's Rights' section except that it applies to a group of users instead of a single user. By default, there is only one group in the system, to which every new user is added to by default. The default group is named, 'default'. Only users which have logged-in to the QMS system will be displayed in the 'Group Members' window.

To create a new group, specify a new group name in the 'Group' window under 'Core Settings' and select the 'Add Group' button, then save the changes.

Core Settings | Group Rights | Event Scope | Addresses | Miscellaneous

Group default loaded.

default

Add Group Edit Group Remove Group

The group 'default' is special. When users are created they are automatically assigned to the 'default' group. The rights, etc assigned to this group determine a user's initial rights and settings.

**CORE SETTINGS**

Group: default

Group Members

admin

Remove Selected Member

Member: (no users) Add

User's may be added to any selected group, and must be selected from the drop-down window next to the 'add' button. **Only users which do not currently belong to a group will be listed.** If a user is to be moved from one group to another, they must first be removed from a group before they can be added to a second. A user may only belong to one group at a time.

The Group Rights, Event Scope, Addresses, and Miscellaneous tabs are identical to the 'User Rights' tabs of the same name, except that they modify the entire group, instead of a single user.

It is of note that these sections may be more useful than the individual 'User's Rights' tabs for large systems. Organizing a system into different user groups allows the admin to quickly modify and specify settings for multiple users and simplify the management process.

If a group address exists in the system, (i.e. sales@domain.com), the admin create a group for sales, and add the sales@domain.com address to the managed address section of the group. Having the group manage the address causes mail to that address to show up in the quarantine and digest for each user in that group.

## Globals

The 'Globals' tab holds settings which affect the entire QMS system. Only administrators have access to the Global settings.

### Login

The 'Login' tab allows customization for the QMS interface. If an administrator wishes to modify the HTML of the default pages, (found under ...gwava/services/qms/http), they may use the original as a template, then specify their modified page as the default page. Modifying the HTTP and Digest release pages is not a supported function, and it is highly recommended to make a copy and archive of the modified page, as updates to the system may copy over any originally named pages present.

Login Deletion BCC Tutorials Authentication Pruning Miscellaneous

HTTP default page [default]  
Set the default page that is loaded when a user browses to the QMS web server. Changes to this setting require the QMS server process to be restarted.

Digest release page [default]  
Set the shtml page to be linked from the digest release button

User Account Expiration 30  
All accounts in the system that have been inactive for longer than this value (in days) will be deleted. This cleanup occurs every time a user logs into the QMS system. A value of 0 disables expiration.

Disable New Accounts ☐  
Selecting this option prevents any users from creating new accounts. Currently existing accounts will continue to function, and GWAVAMAN admins will not be affected by this setting

Prohibited Logins

Remove Selected Address

Address  Add

User accounts may also have an account expiration enforced, which will delete accounts which have been inactive for the specified time period.

The administrator also has the ability to restrict the users which have rights to log into QMS. If the 'Disable New Accounts' option is checked, QMS will not allow any users to log in if they are not in the established users list. If an undesired user is in the established list, enabling this option then removing that user from the user list will block that user from logging into QMS.

### Deletion

Login Deletion BCC Tutorials Authentication Pruning Miscellaneous

A message consists of two items: the message information record and the message source files.

**Users without Administrative Rights**  
When a user without administrative rights deletes a message, they no longer see the message. In addition the following actions may be selected for 'unused' messages - messages that have been deleted by all of the recipients in the QMS system.

Remove Unused Message Information Record ☒

Remove Unused Message Source Files ☒

**Users with Administrative Rights**  
When a user with administrative rights deletes a message, the message can no longer be accessed by non-administrative users. In addition, the following actions may be selected.

Remove Message Information Record ☒

Remove Message Source Files ☒

Globally, the ability to delete a message, and what happens to messages that are deleted, can be set here. By default, all options are selected. If an administrator wishes to keep all mail records visible to the administrator account, even after they are 'deleted' from user accounts, then they should uncheck both Remove the informational record, and the source files, so that the message is not removed from the main database. These settings can be for both administrators and non administrator accounts.

## BCC

QMS can send a blind carbon copy to any specified address when a message is released. This can be used to monitor what kind of mail is released and for what reason. The 'training' offered by BCC is antiquated and is no longer needed for new systems running the Signature spam engine. Training options and use of BCC is held over for upgraded systems only.

To enable BCC, place a checkmark in the enable BCC box, then specify the desired destination address and save changes.

Login	Deletion	BCC	Tutorials	Authentication	Pruning	Miscellaneous
As each message is released (from the digest or from the QMS interface), you may BCC (blind carbon copy) another mailbox or mailboxes. This can aid the initial training process, giving you a quick population of misidentified non-spam.						
Enable BCC on release		<input type="checkbox"/>				
BCC e-mail addresses		<input type="text"/>				

## Tutorials

The link to the tutorials on how to use the system may be removed from the quarantine system. Checking the provided box and saving changes will remove this from QMS pages.

Login	Deletion	BCC	Tutorials	Authentication	Pruning	Miscellaneous
By default, users have an option to view video tutorials available on the upper right of their browser window, next to Logout. You may suppress this option, if desired						
Hide the Tutorial link		<input type="checkbox"/>				

## Authentication

The SMTP authentication address is specified here. The connection address to the GWIA or SMTP must be correct and open on port 25 for authentication to work correctly. If the SMTP requires a specific authentication method, select it below, otherwise leave the setting as the default 'Auto-detect'.

Login	Deletion	BCC	Tutorials	Authentication	Pruning	Miscellaneous
Set the authentication server (typically the GroupWise GWIA) and authentication method here. These settings are identical to the Configure Server options in GWAVAMAN.						
QMS SMTP Authentication Server		<input type="text" value="127.0.0.1"/>				
QMS SMTP Authentication Method		<input type="text" value="Auto-detect"/>				

An alternate port for the SMTP may be specified, using a colon then the port number after the IP address, i.e. for port 24, specify the address as follows:

10.1.1.100:24

## Pruning

QMS is a light database system meant to service a revolving level of temporarily quarantined mail. The amount of mail kept in quarantine is usually specified by a time frame, in days, instead of size. Since it is assumed that mail sent to quarantine is unwanted, a generous default time frame of 30 days is set to allow users to access and release any wanted mail. All the rest of the unwanted mail will be permanently deleted from the system after it eclipses the age limit.

The screenshot shows the 'Pruning' tab in the GWAVAMAN interface. It contains a table with the following settings:

Set the pruning options for removing old messages server here. These settings are identical to the Configure Server options in GWAVAMAN.	
Enable QMS data pruning	<input checked="" type="checkbox"/>
Days to retain messages in QMS	30 days
Prune stored messages	<input checked="" type="checkbox"/>
Prune database entries	<input checked="" type="checkbox"/>

If messages and database entries are desired not to be removed from the system, uncheck the appropriate options and save the changes. Be warned, since QMS was not designed to be a long-term E-Mail archive, such use of the mail system is unsupported and the database may become slow and unstable when the database size exceeds design considerations. Normal pruning of the database system will prevent instability.

## Miscellaneous

To keep the quarantine system from suffering under extensive searches, and to return results quickly, a maximum query number may be specified. No search function will continue after the specified record amount has been reached. The default is 1000. Search results above this number are unmanageable and waste system resources.

The screenshot shows the 'Miscellaneous' tab in the GWAVAMAN interface. It contains a single setting:

Set the miscellaneous options for the quarantine system here.	
Maximum allowable search result items (will take effect after logging back in)	1000 records

## Tools

QMS contains tools to help the administrator manage and generate reports on the quarantine system. All tools are located here under the tools tab.

General information about the system can be gathered into a simple report by selecting the desired report type and then clicking 'Go'.


The screenshot shows the 'Reports' page in the GWAVAMAN interface. It has a green header with tabs: Quarantine, Options, Digest, Users, Groups, Globals, and Tools. The 'Tools' tab is selected. The page lists several report types, each with a dropdown menu and a 'Go' button:

- Activity Report**: Least active users (dropdown), Go
- Group Membership Report**: default (dropdown), Go
- Group Information**: Lists a specific group and basic details. default (dropdown), Go
- Users with related ownership of addresses**: Lists all users that share a Primary Address or a secondary address. Go
- User Information**: Lists a specific user and basic details. admin (dropdown), Go
- Administrative Users**: Lists all users that have an administrative account. Does not include GWAVAMAN administrators that have never accessed the QMS system. Go

## Appendix

### Padlock State Checkboxes

The locks you see next to the options are always visible on the Antivirus scanning settings, but are invisible, and unavailable to configure for the rest of the system, unless you enable the option “**Show Extended Padlock State Checkboxes**”. To Enable the checkboxes and Inheritance, you must have them set to display in the ‘Preferences’ menu, accessed through the preferences icon close to the save button at the top of the GWAVA Management window.



Select the options desired, select ‘Save’, then refresh the current page to expose the new options.




The four state checkbox allows setting the ‘gold locks’ on any checkbox in the rest of the system. A closed lock indicates an overriding option. (This overrides any exceptions or settings in the rest of the system.) Four state locks are a powerful option and they are not standard in any area except in the Antivirus section. The image shown here is set to always block, but not quarantine, but the block is locked. For the events that these settings are active for, the messages will always be blocked, regardless of exceptions or other actions that are active on that message.

### Policy Inheritance

Policies can be set to force their settings to every child policy below them on the policy tree. The Inheritance setting is accessed through the blue policy tree icon.



Selecting inheritance offers three different settings: Allow, Deny, and Force. Allowing inheritance replicates parent policy settings to the child, but allows the child policy to change those settings if desired. Forcing inheritance replicates the associated policy setting in the child policy, and child policies cannot change the setting. Denied inheritance does not replicate any settings from parent to any sub policy in the tree.



## Scanner Configuration: Hierarchy and Inheritance

The GWAVA policy system includes a strict hierarchal system, complete with inheritance, to help in configuration of mail systems.


Scanning configurations in the policy tree, with sub-policies, parent policies, and root policies, creates an easy way to control message scanning settings for any particular message or group. Using this structure for the policy tree also may add an increased need for configurations in complex systems.

A simple example of this can come when separating inbound and outbound message scanning. In the example, Widgets Inc. has separated their mail scanning into two separate policies to independently scan messages coming into and leaving the mail system.


In the example, the inbound system is using antispam, antivirus and some attachment filters to prevent known and yet to be detected problems from entering the system. Outbound scanning is limited to antivirus and the same set of attachment filters.

The two policies are configured nearly identical, where the only difference is that only inbound mail is scanned for spam.

If, at a future point, a new attachment type must be blocked in both inbound and outbound mail, it must be separately added to the configuration of both the inbound and outbound policies. However, this is where inheritance becomes useful.




Scanner hierarchy configuration is usually hidden by default, and must be exposed before it can be modified. To access the hierarchy and inheritance settings, select the 'preferences' button at the top right of the user interface, and check the 'Display policy inheritance icons' box. Save the setting before closing the preferences box.



To apply the desired attachment block to both policies at the same time, the shared configuration components should be moved to the root or parent policy, the 'Widgets Inc.' policy in the example. To do so, the parent policy must have the 'policy contains scanner' option set 'on'. With an active scanner, the parent policy can now contain 'umbrella' settings which will transfer to all sub-policies the parent contains.

In the scanner view, the new attachment type can be added to the block list for the Widgets Inc. policy. These attachments types and items are to be blocked regardless of the message direction. To begin, add the forbidden items to the attachment type list. For this example, \*.com and \*.pif files are added.


(Note that the subordinate, inbound and outbound policy's scanning configuration is located within the Widgets Inc. parent policy.)



While configuring this service, you will now see new icons which were exposed when the inheritance setting was enabled. The icons, left to right, are:  
 Inheritance settings  
 Inheritance status, (Not inherited is shown)  
 Reset to default  
 Enable service checkbox



The inheritance setting has three options.



**Allow inheritance:** This is the default setting for every setting. Simply enabling inheritance causes the same setting to be duplicated through any and all child or sub policies, but still allows the sub-policy to have change this setting independently if required.

**Deny inheritance:** Denying inheritance causes the parent policy's setting to not affect the settings of any and all child policies.


**Force inheritance:** Forcing inheritance causes child policies to use the parent's configured policy. This is useful when certain scanning configurations must be followed or a setting cannot change. All lower policies will be forced to accept and use the parent policy setting.

The example now shows the attachment type scanning enabled and the inheritance forced to prevent accidental disabling of the service later on.

After saving the settings, expand the 'Inbound' scanner and look at the attachment type settings which are in effect.

Because the attachment scanning was set in the parent policy, the same settings are inherited by default in the child policies. The grayed-out settings shown here are the duplicated settings from the parent.

Because the attachment filtering was setup at a higher level, and the setting was configured to 'force inheritance' in the parent policy, enabling or disabling the setting is 'locked'. This is indicated by the yellow padlock. Because it is grayed-out, these settings cannot be changed or configured at this level. The inheritance icon also includes a green arrow, indicating that this setting was inherited from the parent policy.



All of the grayed-out items are locked and cannot be manipulated here, because they are set in the parent policy. However, simply because the setting is locked does not mean that additional filters cannot be created and enabled. For the inbound filter, an additional file type has been added, the \*.exe filter. This filter is only active for the inbound, and is not replicated in the outbound.

Inheritance can also be used to create independent sub-policies to implement specialized filters for specific messages and addresses defined in a policy qualification. The sub-policies will contain all of the scanner settings from the main policy, but can have additional filters applied which do not affect the parent policy. These filters might include surveillance for particular addresses or additional limits imposed on specific users or groups.



## **GWIA and SMTP interfaces on the same box:**

<http://support2.gwava.com/kb/?View=entry&EntryID=1215>

## **SMTP interface ports**

If the GWAVA SMTP interface is set behind a firewall, or multiple firewalls, the following ports should be open for mail flow and GWAVA functions or services:

- 80 – TCP Outbound (Updates services for Antivirus, Signature Engine, and GWAVA system.)
- 21 – FTP Outbound (OS updates)
- 53 – UDP (DNS lookups)
- 25 – TCP Inbound (Used for Mail)
- 25 – TCP Outbound (Only if scanning outbound mail)
- 123 – TCP Outbound (Network Time Protocol (NTP))

The following should be open to access the GWAVA appliance from outside the network:

- 49285 – TCP Inbound (QMS message release service)
- 49282 – TCP Inbound (GWAVA Management Console)
- 22 – TCP (SSH access. This can be a security concern, but may be necessary to enable for support access.)

## GroupWise paths

### Linux

The Linux configuration files are found, by default, in /opt/novell/groupwise/agents/share. If the mail system files are not setup according to default, search the system for the correct file name(s) requested in the interface setup wizard. (ie. For Linux, search for 'gwia.cfg'. Search in the likely GroupWise file structure to shorten the search time.)

## Squid configuration file changes

There are ten lines which need to be added to the squid configuration file for GWAVA to function with the ICAP connection. Add the following:

```
#icap_log /var/log/squid/icap.log

icap_enable on

icap_send_client_username on

icap_client_username_encode off


icap_service service_req reqmod_precache bypass=0 icap://IP Address of GWAVA
server):1344/request

adaptation_access service_req allow all


icap_service service_resp respmod_precache bypass=0 icap://<IP Address of GWAVA
server>:1344/response

adaptation_access service_resp allow all


#turn off persistent connections to increase speed

server_persistent_connections off
```

For specific file and further information, see <http://www.squid-cache.org/Doc/config/> and the GWAVA knowledgebase found at <http://support.gwava.com> for configuration options and explanations.